# **Product datasheet**

Specifications





Head for push button, Harmony XB5, XB4, pushbutton harsh environment, white, without marking

ZB5AC180

#### Main

| Range Of Product                | Harmony XB5                           |  |
|---------------------------------|---------------------------------------|--|
| Product Or Component Type       | Head for push-button                  |  |
| Device Short Name               | ZB5                                   |  |
| Bezel Material                  | Black plastic                         |  |
| Head Type                       | Standard                              |  |
| Mounting Diameter               | 22 mm                                 |  |
| Sale Per Indivisible Quantity   | 1                                     |  |
| Shape Of Signaling Unit Head    | Round                                 |  |
| Type Of Operator                | spring return                         |  |
| Operator Additional Information | Vertical mounting Horizontal mounting |  |

## Complementary

| Cad Overall Width                     | 37 mm   |
|---------------------------------------|---|
| Cad Overall Height                    | 18.5 mm   |
| Cad Overall Depth                     | 37 mm   |
| Net Weight                            | 0.024 kg  |
| Resistance To High Pressure<br>Washer | 90 Pa at 82.5 °C  |
| Operator Profile                      | White flush, unmarked   |
| Mechanical Durability                 | 10000000 cycles   |
| Electrical Composition Code           | C1 for <9 contacts using single blocks in front mounting C2 for <9 contacts using single and double blocks in front mounting C11 for <3 contacts using single blocks in front mounting C15 for <1 contacts using single blocks in front mounting SF1 for <3 contacts using single blocks in front mounting SR1 for <3 contacts using single blocks in rear mounting |
| Device Presentation                   | Basic element   |

#### **Environment**

| Ambient Air Temperature For Storage   | -4085 °C                                |
|---------------------------------------|---|
| Ambient Air Temperature For Operation | -4070 °C                                |
| Electrical Shock Protection Class     | Class II conforming to IEC 61140        |
| Ip Degree Of Protection               | IP66 conforming to IEC 60529 IP69K IP67 |

23 Apr 2024 Life Is On Schneider

| Nema Degree Of Protection | NEMA 4 conforming to UL 508<br>NEMA 13<br>NEMA 12                                     |  |
|---------------------------|---|--|
| Ik Degree Of Protection   | IK03 conforming to IEC 62262  |  |
| Standards                 | UL 508<br>IEC 60947-5-1<br>IEC 60947-1<br>CSA C22.2                                   |  |
| Product Certifications    | CSA<br>UL<br>CE   |  |
| Vibration Resistance      | on Resistance 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6                           |  |
| Shock Resistance          | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |  |

# **Packing Units**

| Unit Type Of Package 1       | PCE    |
|------------------------------|--------|
| Number Of Units In Package 1 | 1      |
| Package 1 Height             | 3.7 cm |
| Package 1 Width              | 3.7 cm |
| Package 1 Length             | 3.7 cm |
| Package 1 Weight             | 24.0 g |

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance


| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>②</b> | Toxic Heavy Metal Free     |     |
| <b>9</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| China Rohs Regulation    | China RoHS declaration  |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |

## **Dimensions Drawings**


#### **Dimensions**



#### Mounting and Clearance


#### Installation on Flat Surface

#### Without Protective Guard



(1) Ø22.5 mm recommended (Ø22.3  $_0^{+0.4}$ ) / Ø0.89 in. recommended (Ø0.88  $_0^{+0.016}$ )

#### With Protective Guard



(1) Ø22.5 mm recommended (Ø22.3  $_0^{+0.4}$ ) / Ø0.89 in. recommended (Ø0.88  $_0^{+0.016}$ )

# **Product datasheet**

## **ZB5AC180**

**Technical Description** 

**Electrical Composition Corresponding to Code C1** 



**Electrical Composition Corresponding to Code C2** 



# **Product datasheet**

## **ZB5AC180**

**Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1** 



#### **Electrical Composition Corresponding to Code C15**





1 N/C



1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C



#### Legend

Single contact



Double contact



Light block



Possible location

