



switch-disconnector Compact INS250 - 160 A - 4 poles

31105

Main

ComPact
Switch disconnector
ComPacT INS
4P
AC
DC
50/60 Hz
AC-22A: 160 A AC 50/60 Hz 220/240 V
AC-22A: 160 A AC 50/60 Hz 380/415 V
AC-22A: 160 A AC 50/60 Hz 440/480 V
AC-22A: 160 A AC 50/60 Hz 480 V NEMA
AC-22A: 160 A AC 50/60 Hz 500/525 V
AC-22A: 160 A AC 50/60 Hz 660/690 V
AC-23A: 160 A AC 50/60 Hz 220/240 V
AC-23A: 160 A AC 50/60 Hz 380/415 V
AC-23A: 160 A AC 50/60 Hz 440/480 V
AC-23A: 160 A AC 50/60 Hz 480 V NEMA
AC-23A: 160 A AC 50/60 Hz 500/525 V
AC-23A: 160 A AC 50/60 Hz 660/690 V
DC-22A: 160 A DC 125 V 2 poles in series
DC-22A: 160 A DC 250 V 4 poles in series
DC-23A: 160 A DC 125 V 2 poles in series
DC-23A: 160 A DC 250 V 4 poles in series
750 V AC 50/60 Hz
160 A at 60 °C
30 kA switch-disconnector alone 690 V AC at 50/60 Hz
330 kA with upstream protection circuit breaker 690 V AC at 50/60 Hz
250 V DC
690 V AC 50/60 Hz
Yes
Yes
No
3

Complementary

Control Type	Direct front rotary handle
Handle Colour	Black
Mounting Mode	Fixed
Mounting Support	Rail Plate

Upside Connection	Front
Downside Connection	Front
Maximum Power	AC-23: 110 kW at 500/525 V AC 50/60 Hz
	AC-23: 45 kW at 220/240 V AC 50/60 Hz
	AC-23: 45 kW at 230 V AC 50/60 Hz (NEMA)
	AC-23: 75 kW at 380/415 V AC 50/60 Hz
	AC-23: 90 kW at 440 V AC 50/60 Hz
	AC-23: 90 kW at 480 V AC 50/60 Hz (NEMA)
	AC-23: 90 kW at 660/690 V AC 50/60 Hz
Rated Duty	Uninterrupted
[Icw] Rated Short-Time Withstand	1.8 kA during 30 s conforming to IEC 60947-3
Current	2.2 kA during 20 s conforming to IEC 60947-3
	4.9 kA during 3 s conforming to IEC 60947-3
	8.5 kA during 1 s conforming to IEC 60947-3
Mechanical Durability	15000 cycles
Electrical Durability	AC-22A: 1500 cycles 440 V AC 50/60 Hz
-	AC-22A: 1500 cycles 500 V AC 50/60 Hz
	AC-22A: 1500 cycles 690 V AC 50/60 Hz
	AC-23A: 1500 cycles 440 V AC 50/60 Hz
	AC-23A: 1500 cycles 500 V AC 50/60 Hz
	AC-23A: 1500 cycles 690 V AC 50/60 Hz
	DC-22A: 1500 cycles 250 V DC 4 poles in series
	DC-23A: 1500 cycles 250 V DC 4 poles in series
Connection Pitch	35 mm
Height	136 mm
Width	140 mm
Depth	96 mm
Net Weight	2.2 kg
Environment	
Standards	IEC 60947-3 IEC 60947-1
Product Certifications	KEMA-KEUR
	CCC
p Degree Of Protection	IP40 conforming to IEC 60529
lk Degree Of Protection	IK07 conforming to EN 50102
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-5085 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	16.9 cm
Package 1 Width	13.8 cm
Package 1 Length	16.0 cm
Package 1 Weight	2.422 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	9
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm

Package 2 Length	60.0 cm
Package 2 Weight	22.573 kg

Contractual warranty

Warranty 12 months

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

4 May 2024