



Micrologic 6.0 A trip unit - LSIG for NT fixed, NW 08..63 fixed

47286

Main

Iviaiii	
Range	MasterPact
Range Of Product	MasterPact NT
	MasterPact NW
Product Or Component Type	Control unit
Trip Unit Name	MicroLogic 6.0 A
Trip Unit Technology	Electronic
Range Compatibility	Masterpact NT0616
	Masterpact NW0840
	Masterpact NW40b63
Device Application	Distribution
Number Of Poles	4P
	3P
Protected Poles Description	4t
	3t
	3t + N/2
Trip Unit Protection Functions	Selective + earth-fault protection
Protection Type	for overload protection (long time)
	for short time short-circuit protection
	for instantaneous short-circuit protection
	for earth fault
Trip Unit Rating	630 A at 50 °C
	800 A at 50 °C
	1000 A at 50 °C
	1250 A at 50 °C
	1600 A at 50 °C
	2000 A at 50 °C
	2500 A at 50 °C
	3200 A at 50 °C
	4000 A at 50 °C
	5000 A at 50 °C
	6300 A at 50 °C
Network Type	AC
Network Frequency	50/60 Hz
Circuit Breaker Mounting Mode	Fixed

Complementary

Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable 9 settings
[Ir] Long-Time Protection Pick-Up Adjustment Range	0.41 x ln
Long-Time Protection Delay Adjustment Type Tr	Adjustable 9 settings

[Tr] Long-Time Protection Delay Adjustment Range	0.716.6 s at 7.2 x lr
Aujustinent Kange	0.724 s at 6 x lr 12.5600 s at 1.5 x lr
Thermal Memory	20 mn
Short-Time Protection Pick-Up Adjustment Type Isd	Adjustable 9 settings
[Isd] Short-Time Protection Pick- Up Adjustment Range	1.510 x lr
Short-Time Protection Delay Adjustment Type Tsd	Adjustable
[Tsd] Short-Time Protection Delay Adjustment Range	00.4 s l²t=off 0.10.4 s l²t=on
Instantaneous Protection Pick-Up Adjustment Type Ii	Adjustable 9 settings
[li] Instantaneous Protection Pick- Up Adjustment Range	215 x In Off
Ground-Fault Protection Pick-Up Adjustment Type Ig	Adjustable 9 settings
[lg] Ground-Fault Protection Pick- Up Adjustment Range	0.21 x In for 400 A < In < 1250 A 0.31 x In for In <= 400 A 5001200 A for In >= 1250 A
Ground-Fault Protection Time Delay Adjustment Type Tg	Adjustable
[Tg] Ground-Fault Protection Time Delay Adjustment Range	00.4 s l²t=off 0.10.4 s l²t=on
Earth-Leakage Protection	Without
Zone Selective Interlocking Zsi	With
Zone Selective Interlocking Zsi Local Signalling	With 3 LEDs (red) for electrical fault 1 LED (red) for internal error
	3 LEDs (red) for electrical fault
Local Signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Local Signalling Display Type	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display
Local Signalling Display Type Type Of Measurement	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout
Local Signalling Display Type Type Of Measurement Communication Of Data	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For Operation Ambient Air Temperature For	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For Operation Ambient Air Temperature For Storage	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For Operation Ambient Air Temperature For Storage Packing Units	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings -2570 °C -4085 °C
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For Operation Ambient Air Temperature For Storage Packing Units Unit Type Of Package 1	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings -2570 °C -4085 °C
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For Operation Ambient Air Temperature For Storage Packing Units Unit Type Of Package 1 Number Of Units In Package 1	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings -2570 °C -4085 °C
Local Signalling Display Type Type Of Measurement Communication Of Data Environment Ambient Air Temperature For Operation Ambient Air Temperature For Storage Packing Units Unit Type Of Package 1 Number Of Units In Package 1 Package 1 Height	3 LEDs (red) for electrical fault 1 LED (red) for internal error Digital display Ammeter Measurement readout Protection and alarm settings -2570 °C -4085 °C PCE 1 6.8 cm

Contractual warranty

Warranty 12 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information