Product datasheet

Specifications





TeSys K contactor - 3P - AC-3 <= 440 V 6 A - 1 NO aux. - 230 V AC coil

LC1K06107P7

Main

Range	TeSys
Product Or Component Type	Contactor
Device Short Name	LC1K
Device Application	Control
Contactor Application	Motor control

Complementary

Complementary	
Utilisation Category	AC-3
	AC-3e
	AC-4
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC <= 400 Hz
	Signalling circuit: <= 690 V AC <= 400 Hz
[le] Rated Operational Current	6 A (at <60 °C) at <= 440 V AC AC-3 for power circuit
	6 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
Control Circuit Type	AC at 50/60 Hz
[Uc] Control Circuit Voltage	230 V AC 50/60 Hz
Motor Power Kw	1.5 kW at 220230 V AC 50/60 Hz AC-3
	2.2 kW at 380415 V AC 50/60 Hz AC-3
	3 kW at 440/690 V AC 50/60 Hz AC-3
	1.5 kW at 220230 V AC 50/60 Hz AC-3e
	2.2 kW at 380415 V AC 50/60 Hz AC-3e
	3 kW at 440/690 V AC 50/60 Hz AC-3e
	1.5 kW at 220230 V AC 50/60 Hz AC-4
	2.2 kW at 380415 V AC 50/60 Hz AC-4
	3 kW at 440/690 V AC 50/60 Hz AC-4
Auxiliary Contact Composition	1 NO
[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air	20 A (at 60 °C) for power circuit
Thermal Current	10 A (at 50 °C) for signalling circuit
Irms Rated Making Capacity	110 A AC for power circuit conforming to IEC 60947
	110 A AC for signalling circuit conforming to IEC 60947
Rated Breaking Capacity	110 A at 220230 V conforming to IEC 60947
	110 A at 380400 V conforming to IEC 60947
	110 A at 415 V conforming to IEC 60947
	110 A at 440 V conforming to IEC 60947
	80 A at 500 V conforming to IEC 60947
	70 A at 660690 V conforming to IEC 60947
	-

[Icw] Rated Short-Time Withstand	90 A 50 °C - 1 s for power circuit
Current	85 A 50 °C - 5 s for power circuit
	80 A 50 °C - 10 s for power circuit 60 A 50 °C - 30 s for power circuit
	45 A 50 °C - 1 min for power circuit
	40 A 50 °C - 3 min for power circuit
	20 A 50 $^{\circ}$ C - >= 15 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit
Associated Fuse Rating	25 A gG at <= 440 V for power circuit
	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit: 600 V conforming to UL 508
	Power circuit: 690 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-5-1 Signalling circuit: 600 V conforming to UL 508
	Power circuit: 600 V conforming to CSA C22.2 No 14
	Signalling circuit: 600 V conforming to CSA C22.2 No 14
Insulation Resistance	> 10 MOhm for signalling circuit
Inrush Power In Va	
	30 VA (at 20 °C)
Hold-In Power Consumption In Va	4.5 VA (at 20 °C)
Heat Dissipation	1.3 W
Control Circuit Voltage Limits	Operational: 0.81.15 Uc (at <50 °C) Drop-out: >= 0.20 Uc (at <50 °C)
Connections - Terminals	Faston terminals 2 cable(s) (external diameter: 2.8 mm) Faston terminals 1 cable(s) (external diameter: 6.35 mm)
Maximum Operating Rate	3600 cyc/h
Auxiliary Contacts Type	type instantaneous 1 NO
Signalling Circuit Frequency	<= 400 Hz
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Mounting Support	Plate
	Rail
Operating Time	10 20 ms coil de-energisation and NO opening
Operating Time	1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing
	1020 ms coil energisation and NO closing
Operating Time Safety Reliability Level	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	1020 ms coil energisation and NO closing
	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
Safety Reliability Level	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Safety Reliability Level Non Overlap Distance Mechanical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles
Safety Reliability Level	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability Mechanical Robustness	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Safety Reliability Level Non Overlap Distance Mechanical Durability Electrical Durability	1020 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 0.5 mm 10 Mcycles 1.3 Mcycles 6 A AC-3 at Ue <= 440 V

Depth	57 mm
Net Weight	0.18 kg

Environment

Environment		
Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1	
Product Certifications	CB Scheme CCC UL CSA EAC CE UKCA	
Ip Degree Of Protection	IP2X conforming to VDE 0106	
Protective Treatment	TC conforming to IEC 60068 TC conforming to DIN 50016	
Ambient Air Temperature For Storage	Air Temperature For -5080 °C	
Operating Altitude	2000 m without derating	
Flame Retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	6.2 cm
Package 1 Length	6.6 cm
Package 1 Weight	180.0 g

Contractual warranty

Warranty

12 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information