# **Product datasheet**

Specification





# TeSys LRF - electronic thermal overload relay - 132...220 A - class 10

LR9F5371

! Discontinued on: 31 Dec 2023

① To be discontinued

### Main

Range	TeSys
Product Name	TeSys LRF
Device Short Name	LR9F
Product Or Component Type	Electronic thermal overload relay
Relay Application	Motor protection
Product Compatibility	LC1F185LC1F265
Network Type	AC
Thermal Overload Class	Class 10 conforming to IEC 60947-4
Thermal Protection Adjustment Range	132220 A

## **Complementary**

50/60 Hz
Direct on contactor Plate
1.12 +/- 0.06 In tripping conforming to IEC 60947-4-1
4 kV conforming to IEC 61000-4-5
1 NO + 1 NC
5 A for control circuit
1000 V AC 50/60 Hz for power circuit conforming to VDE 0110 group C
Power circuit: 1000 V AC conforming to IEC 60947-4
8 kV conforming to IEC 60947-1
Tripping in 4 s +/- 20 % conforming to IEC 60947-4-1
Manual reset on front relay
Dial white full-load current adjustment Test button red Push-button red reset Push-button stop
Trip indicator
-2070 °C
<= 5 mA no-load
0150 mA
<2.5 V closed state

Connections - Terminals  Tightening Torque	Control circuit: screw clamp terminals 1 cable 0.752.5 mm² - cable stiffness: flexible - with cable end  Control circuit: screw clamp terminals 1 cable 0.752.5 mm² - cable stiffness: solid  Control circuit: screw clamp terminals 1 cable 0.754 mm² - cable stiffness: flexible - without cable end  Control circuit: screw clamp terminals 2 cable 11.5 mm² - cable stiffness: flexible - with cable end  Control circuit: screw clamp terminals 2 cable 12.5 mm² - cable stiffness: flexible - without cable end  Control circuit: screw clamp terminals 2 cable 1 mm² - cable stiffness: solid  Power circuit: lugs-ring terminals M10  Control circuit: 1.2 N.m on screw clamp terminals  Power circuit: 35 N.m on screw clamp terminals
Height ————————————————————————————————————	101 mm
Width	115 mm
Depth	123.5 mm
Net Weight	0.95 kg
Environment	
Standards	IEC 60255-17 IEC 60947-4-1 IEC 60255-8 VDE 0660 EN 60947-4-1
Product Certifications	UL CSA UKCA
Protective Treatment	ТН
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP20 conforming to VDE 0106
Ambient Air Temperature For Operation	-2055 °C conforming to IEC 60255-8
Ambient Air Temperature For Storage	-4085 °C
Operating Altitude	<= 2000 m without derating
Fire Resistance	850 °C conforming to IEC 60695-2-1
Mechanical Robustness	Shocks: 13 Gn for 11 ms conforming to IEC 60068-2-7 Vibrations 5300 Hz: 2 GN conforming to IEC 60068-2-6
Dielectric Strength	6 kV 50 Hz conforming to IEC 255-5
Electromagnetic Compatibility	Resistance to electrostatic discharge: 6 kV in indirect mode conforming to IEC 61000-4-2 Resistance to electrostatic discharge: 8 kV in air conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test: 10 V/m conforming to IEC 61000-4-3 Fast transients immunity test: 2 kV conforming to IEC 61000-4-4
Packing Units	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.000 cm
Package 1 Width	16.500 cm

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.000 cm
Package 1 Width	16.500 cm
Package 1 Length	13.000 cm
Package 1 Weight	1.035 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	11

Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	12.030 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	44
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	59.048 kg

# **Contractual warranty**

Warranty 12 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>Ø</b>	Mercury Free	
	Rohs Exemption Information	Yes
<b>②</b>	Pvc Free	

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information