Product datasheet





motor controller LTMR TeSys T -100..240 V AC 8 A for Ethernet TCP/IP

LTMR08EFM

Main

Range	TeSys
Product Name	TeSys T
Device Short Name	LTMR
Product Or Component Type	Motor controller
Device Application	Equipment monitoring and control
Measurement Current	0.48 A
[Us] Rated Supply Voltage	100240 V AC 50/60 Hz
Current Consumption	862.8 mA
Supply Voltage Limits	93.5264 V AC
Communication Port Protocol	Modbus TCP/EtherNet/IP
Bus Type	Ethernet IEEE 802.3 interface, addressing 0159, transmission rate 10100 Mbit/s, RJ45 with 2 shielded twisted pairs

omplomentary

Complementary	
[Ui] Rated Insulation Voltage	690 V conforming to EN/IEC 60947-1 690 V conforming to CSA C22.2 No 14 690 V conforming to UL 508
[Uimp] Rated Impulse Withstand Voltage	4 kV supply, inputs and outputs conforming to EN/IEC 60947-4-1 6 kV current or voltage measurement circuit conforming to EN/IEC 60947-4-1 0.8 kV communication circuit conforming to EN/IEC 60947-4-1
Short-Circuit Withstand	100 kA conforming to EN/IEC 60947-4-1
Associated Fuse Rating	4 A gG for output 0.5 A gG for control circuit
Protection Type	Thermal overload protection Overload Thermal protection Locked rotor Phase failure Phase unbalance Load fluctuation Reverse polarity protection Overload (long time) Earth-leakage protection Power factor variation
Network And Machine Diagnosis Type	Trip context information Phase fault and earth fault trip counters Trip history information Event recording Remaining operating time before overload tripping

Life Is On Schneider 19 Apr 2024

Starting current and time Fault recording

Waiting time after overload tripping Running hours counter/operating time Motor control command recording

Logic Input Number	6
Input Current	3.1 mA at 100 V 7.5 mA at 240 V
Current State 0 Guaranteed	Logic input: 040 V and <= 15 mA for 25 ms
Current State 1 Guaranteed	Logic input: 79264 V and >= 2 mA for 25 ms
Maximum Output Switching Frequency	2 Hz
Load Current	5 A at 250 V AC for logic output 5 A at 30 V DC for logic output
Permissible Power	480 VA (AC-15), le = 2 A, 500000 cycles (output) 30 W (DC-13), le = 1.25 A, 500000 cycles (output)
Maximum Operating Rate	1800 cyc/h
Contacts Type And Composition	1 NO + 1 NC fault signal 3 NO
Metering Type	Earth-fault current Imbalance current Temperature Average current lavg Phase current I1, I2, I3 RMS
Measurement Accuracy	515 % earth fault current internal measurement 1 % voltage (100830 V) 3 % power factor 5 % earth fault current external measurement +/- 30 min/year internal clock 0,02 temperature 1 % current 5 % active and reactive power
Overvoltage Category	III
Connection Pitch	5.08 mm
Connections - Terminals	Control circuit: connector 1 cable(s) 0.252.5 mm² (AWG 24AWG 14) flexible with cable end Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) flexible without cable end Control circuit: connector 1 cable(s) 0.252.5 mm² (AWG 24AWG 14) flexible without cable end Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) solid without cable end Control circuit: connector 2 cable(s) 0.21 mm² (AWG 24AWG 14) flexible with cable end Control circuit: connector 2 cable(s) 0.21.5 mm² (AWG 24AWG 14) flexible without cable end Control circuit: connector 2 cable(s) 0.51.5 mm² (AWG 24AWG 14) flexible without cable end Control circuit: connector 2 cable(s) 0.51.5 mm² (AWG 24AWG 14) solid without cable end
Tightening Torque	Control circuit: 0.50.6 N.m flat screwdriver 3 mm
Pollution Degree	3

Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2
Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3
Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4
Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming
to EN/IEC 61000-4-4 Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC
61000-4-11 Conducted PE disturbances 10 V conforming to EN/IEC 61000 4.6
Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6 Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5
Temperature sensor: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5
Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5
Communication: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
Relay outputs and supply: surges (serial mode), 2 kV, conforming to EN/IEC
61000-4-5 Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC
61000-4-5
Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
91 mm
61 mm
122.5 mm
0.53 kg
Web server
LTMR
EN 60947-4-1
IEC 60947-4-1
CSA C22.2 No 14
IACS E10 UL 508
00 300
NOM
LROS (Lloyds register of shipping)
RMRoS
CSA BV
BV KERI
GL
ABS
ATEX
RINA
UL
C-Tick
EAC
CCC
DNV
12 x 24 hour cycles conforming to EN/IEC 60068-2-30
48 h conforming to EN/IEC 60070-2-11
TH conforming to EN/IEC 60068
650 °C conforming to EN/IEC 60695-2-12 960 °C conforming to UL 94
-2060 °C
-4080 °C
<= 2000 m without derating
Vibrations mounted on symmetrical rail: 1 Gn, 5300 Hz conforming to EN/IEC
60068-2-6
Vibrations plate mounted: 4 Gn, 5300 Hz conforming to EN/IEC 60068-2-6 Shocks half sine wave acceleration: 15 Gn for 11 ms conforming to EN/IEC 60068-2-27

Packing Units

Ip Degree Of Protection

IP20

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	7.1 cm
Package 1 Length	13.5 cm
Package 1 Weight	534.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.661 kg

Contractual warranty

Warranty 12 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free
Ø	Rohs Exemption Information Yes
Ø	Pvc Free
Ø	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information