# **Product datasheet**

Specifications





# Motion servo drive, Lexium 32 single phase supply voltage 115/230 V, 0.3/0.5 kW

LXM32SU90M2

## Main

Range Of Product	Lexium 32	
Product Or Component Type	Motion servo drive	
Device Short Name	LXM32S	
Format Of The Drive	Book	
Network Number Of Phases	Single phase	
[Us] Rated Supply Voltage	100120 V - 1510 % 200240 V - 1510 %	
Supply Voltage Limits	85132 V 170264 V	
Supply Frequency	50/60 Hz - 55 %	
Network Frequency	47.563 Hz	
Emc Filter	Integrated	
Continuous Output Current	3 A at 8 kHz	
Output Current 3S Peak	6 A at 115 V for 5 s 9 A at 230 V for 5 s	
Maximum Continuous Power	400 W at 115 V 900 W at 230 V	
Nominal Power	0.3 kW at 115 V 8 kHz 0.5 kW at 230 V 8 kHz	
Line Current	5.2 A 90 % at 115 V, with external line choke of 2 mH 6.3 A 107 % at 230 V, with external line choke of 2 mH 5.4 A 159 % at 115 V, without line choke 4.5 A 166 % at 230 V, without line choke	

## Complementary

Switching Frequency	8 kHz	
Overvoltage Category	III	
Maximum Leakage Current	30 mA	
Output Voltage	<= power supply voltage	
Electrical Isolation	Between power and control	
Type Of Cable	Single-strand IEC cable (temperature: 50 °C) copper 90 °C XLPE/EPR	
Electrical Connection	Terminal, clamping capacity: 3 mm², AWG 12 (CN8)	
Tightening Torque	CN8: 0.5 N.m	
Discrete Input Number	2 capture discrete input(s)	
Discrete Input Type	Capture (CAP terminals)	

Sampling Duration	0.25 ms		
	0.20 1115		
Discrete Input Voltage	24 V DC for capture		
Discrete Input Logic	Positive (compliment of STO_A, compliment of STO_B) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1		
Response Time	<= 5 ms compliment of STO_A, compliment of STO_B		
Discrete Output Number	3		
Discrete Output Type	Logic output(s) (DO)24 V DC		
Discrete Output Voltage	<= 30 V DC		
Discrete Output Logic	Positive or negative (DO) conforming to EN/IEC 61131-2		
Contact Bounce Time	<= 1 ms for compliment of STO_A, compliment of STO_B		
Braking Current	50 mA		
Response Time On Output	250 μs (DO) for discrete output(s)		
Safety Function	STO (safe torque off), integrated		
Safety Level	SIL 3 conforming to EN/IEC 61508		
Communication Interface	Modbus, integrated SERCOS III, integrated		
Connector Type	RJ45 (labelled CN7) for Modbus		
Commissioning Port	2-wire RS485 multidrop for Modbus		
Transmission Rate	9600, 19200, 38400 bps for bus length of 40 m for Modbus		
Number Of Addresses	1247 for Modbus		
Status Led	1 LED (red) servo drive voltage		
Signalling Function	Display of faults 7 segments		
Marking	CE		
Operating Position	Vertical +/- 10 degree		
Product Compatibility	Servo motor BMH (70 mm, 1 motor stacks)		
Width	68 mm		
Height	270 mm		
Depth	237 mm		
Net Weight	1.8 kg		

## **Environment**

Electromagnetic Compatibility	Conducted EMC conforming to EN 55011 class A group 1	
Standards	EN/IEC 61800-3	
Product Certifications	CSA	
Ip Degree Of Protection	IP20 conforming to EN/IEC 60529	
Vibration Resistance	1 gn (f= 13150 Hz) conforming to EN/IEC 60068-2-6	
Shock Resistance	15 gn for 11 ms conforming to EN/IEC 60028-2-27	
Pollution Degree	2 conforming to EN/IEC 61800-5-1	
Environmental Characteristic	Classes 3C1 conforming to IEC 60721-3-3	
Relative Humidity	Class 3K3 (5 to 85 %) without condensation conforming to IEC 60721-3-3	
Ambient Air Temperature For Operation	050 °C conforming to UL	

Ambient Air Temperature For Storage	-2570 °C	
Type Of Cooling	Natural convection	
Operating Altitude	<= 1000 m without derating	

## **Packing Units**

Unit Type Of Package 1 PCE  Number Of Units In Package 1 1  Package 1 Height 10.6 cm  Package 1 Width 27.5 cm  Package 1 Length 33 cm  Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm  Package 3 Length 60 cm	Number Of Units In Package 1 1  Package 1 Height 10.6 cm  Package 1 Width 27.5 cm  Package 1 Length 33 cm  Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Height 80 cm	•	
Package 1 Height         10.6 cm           Package 1 Width         27.5 cm           Package 1 Length         33 cm           Package 1 Weight         2.37 kg           Unit Type Of Package 2         S03           Number Of Units In Package 2         2           Package 2 Height         30 cm           Package 2 Width         30 cm           Package 2 Length         40 cm           Package 2 Weight         5.529 kg           Unit Type Of Package 3         P06           Number Of Units In Package 3         16           Package 3 Height         80 cm           Package 3 Width         80 cm           Package 3 Length         60 cm	Package 1 Height         10.6 cm           Package 1 Width         27.5 cm           Package 1 Length         33 cm           Package 1 Weight         2.37 kg           Unit Type Of Package 2         S03           Number Of Units In Package 2         2           Package 2 Height         30 cm           Package 2 Width         30 cm           Package 2 Length         40 cm           Package 2 Weight         5.529 kg           Unit Type Of Package 3         P06           Number Of Units In Package 3         16           Package 3 Height         80 cm           Package 3 Width         80 cm           Package 3 Length         60 cm	Unit Type Of Package 1	PCE
Package 1 Width 27.5 cm  Package 1 Length 33 cm  Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 1 Width       27.5 cm         Package 1 Length       33 cm         Package 1 Weight       2.37 kg         Unit Type Of Package 2       S03         Number Of Units In Package 2       2         Package 2 Height       30 cm         Package 2 Width       30 cm         Package 2 Length       40 cm         Package 2 Weight       5.529 kg         Unit Type Of Package 3       P06         Number Of Units In Package 3       16         Package 3 Height       80 cm         Package 3 Width       80 cm         Package 3 Length       60 cm	Number Of Units In Package 1	1
Package 1 Length 33 cm  Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 1 Length 33 cm  Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Width 80 cm	Package 1 Height	10.6 cm
Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 1 Weight 2.37 kg  Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 1 Width	27.5 cm
Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Unit Type Of Package 2 S03  Number Of Units In Package 2 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 1 Length	33 cm
Number Of Units In Package 2  Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Number Of Units In Package 2 Package 2 Height 30 cm Package 2 Width 30 cm Package 2 Length 40 cm Package 2 Weight 5.529 kg Unit Type Of Package 3 P06 Number Of Units In Package 3 16 Package 3 Height 80 cm Package 3 Width 80 cm Package 3 Length 60 cm	Package 1 Weight	2.37 kg
Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Height 30 cm  Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Unit Type Of Package 2	S03
Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Width 30 cm  Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Number Of Units In Package 2	2
Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Length 40 cm  Package 2 Weight 5.529 kg  Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Height	30 cm
Package 2 Weight 5.529 kg Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Weight 5.529 kg Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Width	30 cm
Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Unit Type Of Package 3 P06  Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Length	40 cm
Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Number Of Units In Package 3 16  Package 3 Height 80 cm  Package 3 Width 80 cm  Package 3 Length 60 cm	Package 2 Weight	5.529 kg
Package 3 Height 80 cm Package 3 Width 80 cm Package 3 Length 60 cm	Package 3 Height 80 cm Package 3 Width 80 cm Package 3 Length 60 cm	Unit Type Of Package 3	P06
Package 3 Width 80 cm Package 3 Length 60 cm	Package 3 Width 80 cm Package 3 Length 60 cm	Number Of Units In Package 3	16
Package 3 Length 60 cm	Package 3 Length 60 cm	Package 3 Height	80 cm
		Package 3 Width	80 cm
Package 3 Weight 52.124 kg	Package 3 Weight 52.124 kg	Package 3 Length	60 cm
5 5		Package 3 Weight	52.124 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>Ø</b>	Mercury Free	
	Rohs Exemption Information	Yes
<b>②</b>	Pvc Free	

#### **Certifications & Standards**

Circularity Profile	End of Life Information	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Environmental Disclosure	Product Environmental Profile	
China Rohs Regulation	China RoHS declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Reach Regulation	REACh Declaration	


## **Product datasheet**

## **LXM32SU90M2**

## **Dimensions Drawings**

## Lexium 32 Servo Drive


#### **Dimensions**



Mounting and Clearance

#### **Lexium 32 Motion Control Servo Drives**

#### **Mounting Recommendations**



LXM32•U45M2, •U90M2 and LXM32•U60N4 servo drives are cooled by natural convection. LXM32•D18M2, •D30M2, LXM32 •D12N4, •D18N4, •D30N4 and •D72N4servo drives have an integrated fan.

When installing the servo drive in the enclosure, follow the instructions below with regard to the temperature and protection index:

- Provide sufficient cooling of the servo drive
- Do not mount the servo drive near heat sources
- . Do not mount the servo drive on flammable materials
- Do not heat the servo drive cooling air by currents of hot air from other equipment and components, for example from an external braking resistor
- Mount the servo drive vertically (± 10%)
- If the servo drive is used above its thermal limits, control stops due to overtemperature

NOTE: For cables that are connected via the underside of the servo drive, a free space ≥ 200 mm/7.87 in. is required under the unit to comply with the bending radius of the connection cables.

Ambient temperature	Mounting distances	Instructions to be followed
0°C+ 50°C	d ≥ 0 mm	-
+ 50°C+ 60°C	d ≥ 0 mm	Reduce the output current by 2.2% per °C above 50°C

NOTE: Do not use insulated enclosures, as they have a poor level of conductivity.


#### Recommendations for Mounting in an Enclosure

To ensure good air circulation in the servo drive:

- Fit ventilation grilles on the enclosure.
- Ensure that ventilation is adequate, otherwise install a forced ventilation unit with a filter.

#### **Product datasheet**

#### LXM32SU90M2



- (1) Natural convection
- (2) Forced ventilation
  - Any apertures and/or fans must provide a flow rate at least equal to that of the servo drive fans (refer to characteristics).
  - Use special filters with IP 54 protection.

#### Mounting in Metal Enclosure (IP 54 Degree of Protection)

The servo drive must be mounted in a dust and damp proof enclosure in certain environmental conditions, such as dust, corrosive gases, high humidity with risk of condensation and dripping water, splashing liquid, etc. In these cases, Lexium 32 servo drives can be installed in an enclosure where the internal temperature must not exceed 60°C.