# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# joystick controller XKBA - 2 movements - 4 directions

XKBA11207

! Discontinued on: 12 May 2023

### (!) Discontinued

### Main

| Range Of Product             | Harmony XK                   |
|------------------------------|------------------------------|
| Product Or Component Type    | Complete joystick controller |
| Product Specific Application | Light hoisting applications  |

### Complementary

| Complementary                            |   |
|--|---|
| Device Short Name                        | XKB   |
| Bezel Material                           | Metal   |
| Fixing Collar Material                   | Metal   |
| Sale Per Indivisible Quantity            | 1   |
| Protective Treatment                     | TC  |
| Ambient Air Temperature For Storage      | -4070 °C  |
| Ambient Air Temperature For<br>Operation | -2070 °C  |
| Overvoltage Category                     | Class I conforming to IEC 61140   |
| Ip Degree Of Protection                  | IP54 conforming to IEC 60529<br>IP20 conforming to IEC 60529  |
| Standards                                | UL 508<br>CSA C22.2 No 14<br>EN/IEC 60947-5-1   |
| Product Certifications                   | RRS<br>UL<br>CCC<br>CSA   |
| Contact Code Designation                 | A300<br>Q300  |
| Operator Position Information            | All positions   |
| Operator Profile                         | Handle with zero position mechanical interlock  |
| Notch Per Direction                      | 13 notches at 12°-20°-28° for each direction  |
| Mechanical Durability                    | 1000000 cycles  |
| Vibration Resistance                     | 6 gn (f= 170 Hz) conforming to IEC 60068-2-6  |
| Shock Resistance                         | 20 gn (duration = 11 ms) conforming to IEC 60068-2-27   |
| Connections - Terminals                  | Captive screw clamp terminals, $\le$ 2 x 1.5 mm <sup>2</sup> with cable end<br>Captive screw clamp terminals, $\le$ 1 x 2.5 mm <sup>2</sup> without cable end<br>Captive screw clamp terminals, $\ge$ 1 x 0.5 mm <sup>2</sup> |
| Short-Circuit Protection                 | 10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1  |

| [Ith] Conventional Free Air<br>Thermal Current | 10 A conforming to EN/IEC 60947-5-1 10 A conforming to CSA C22.2 No 14 10 A conforming to UL 508 |
|--|--|
| [Ui] Rated Insulation Voltage                  | 500 V (pollution degree 3) conforming to IEC 60947-1   |

## **Packing Units**

| Unit Type Of Package 1       | PCE       |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Weight             | 453.592 g |

### **Sustainability**

Weee

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

### Well-being performance

| Mercury Free               |  |
|----------------------------|--|
| Rohs Exemption Information | Yes  |
| Reach Regulation           | REACh Declaration  |
| Eu Rohs Directive          | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation      | China RoHS declaration                                     |

collection and never end up in rubbish bins

The product must be disposed on European Union markets following specific waste