Product datasheet

Specifications





switch disconnector, Compact INS160, 160 A, with red rotary handle and yellow front, 4 poles

28929

Main

mann		
Range	ComPact	
Product Name	ComPacT INS Switch disconnector	
Product Or Component Type		
Poles Description	4P	
Network Type	AC	
	DC	
Network Frequency	50/60 Hz	
[le] Rated Operational Current	AC-23A: 100 A AC 50/60 Hz 500 V	
	AC-22A: 160 A AC 50/60 Hz 220/240 V	
	AC-22A: 160 A AC 50/60 Hz 380/415 V 2 poles in series	
	AC-22A: 160 A AC 50/60 Hz 440/480 V 2 poles in series	
	AC-22A: 160 A AC 50/60 Hz 500 V 4 poles in series	
	•	
	AC-22A: 160 A AC 50/60 Hz 660/690 V 4 poles in series	
	AC-23A: 100 A AC 50/60 Hz 660/690 V	
	AC-23A: 160 A AC 50/60 Hz 220/240 V	
	AC-23A: 160 A AC 50/60 Hz 380/415 V	
	AC-23A: 160 A AC 50/60 Hz 440/480 V	
	DC-22A: 160 A DC 50/60 Hz 125 V 2 poles in series	
	DC-23A: 160 A DC 50/60 Hz 125 V 2 poles in series	
	DC-22A: 160 A DC 50/60 Hz 250 V 4 poles in series	
	DC-23A: 160 A DC 50/60 Hz 250 V 4 poles in series	
[Ui] Rated Insulation Voltage	750 V AC 50/60 Hz	
[Uimp] Rated Impulse Withstand Voltage	8 KV	
[Ith] Conventional Free Air Thermal Current	160 A at 60 °C	
[Icm] Rated Short-Circuit Making Capacity	154 kA with upstream protection circuit breaker 690 V AC at 50/60 Hz 20 kA switch-disconnector alone 690 V AC at 50/60 Hz	
[Ue] Rated Operational Voltage	250 V DC 690 V AC 50/60 Hz	
Suitability For Isolation	Yes	
Contact Position Indicator	Yes	
Visible Break	No	
Pollution Degree	3	

Complementary

Control Type	Rotary handle
Handle Colour	Red
Mounting Mode	Fixed
Mounting Support	Plate DIN rail

Upside Connection	Front
Downside Connection	Front
Maximum Power	AC-23: 110 kW at 500/525 V AC 50/60 Hz
	AC-23: 45 kW at 220/240 V AC 50/60 Hz
	AC-23: 75 kW at 380/415 V AC 50/60 Hz
	AC-23: 90 kW at 440 V AC 50/60 Hz
	AC-23: 90 kW at 660/690 V AC 50/60 Hz
Rated Duty	Uninterrupted
Intermittent Duty Class	Class 120 - 60 %
Enclosure Dimensions For Ithe	260 mm x 160 mm x 55 mm
[Icw] Rated Short-Time Withstand	0.01 kA during 30 s conforming to IEC 60947-3
Current	1.23 kA during 20 s conforming to IEC 60947-3
	3.175 kA during 3 s conforming to IEC 60947-3
	5.5 kA during 1 s conforming to IEC 60947-3
Mechanical Durability	15000 cycles
Electrical Durability	AC-22A: 1500 cycles 220/240 V AC 50/60 Hz
	AC-22A: 1500 cycles 380/415 V AC 50/60 Hz 4 poles in series
	AC-22A: 1500 cycles 440 V AC 50/60 Hz
	AC-22A: 1500 cycles 500 V AC 50/60 Hz
	AC-23A: 1500 cycles 220/240 V AC 50/60 Hz
	AC-23A: 1500 cycles 380/415 V AC 50/60 Hz
	AC-23A: 1500 cycles 440 V AC 50/60 Hz
	AC-23A: 1500 cycles 500 V AC 50/60 Hz
	DC-22A: 1500 cycles 250 V DC 50/60 Hz 4 poles in series
	DC-23A: 1500 cycles 250 V DC 50/60 Hz 4 poles in series
	AC-22A: 1500 cycles 690 V AC 50/60 Hz
	AC-23A: 1500 cycles 690 V AC 50/60 Hz 4 poles in series
Connection Pitch	30 mm
Height	100 mm
Width	135 mm
Depth	62.5 mm
Net Weight	0.9 kg

Environment

Standards	IEC 60947-3 IEC 60947-1	
Product Certifications	KEMA-KEUR CCC	
Ip Degree Of Protection	IP40 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to EN 50102	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-5085 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.600 cm
Package 1 Width	11.900 cm
Package 1 Length	15.300 cm
Package 1 Weight	1.132 kg
Unit Type Of Package 2	S03

Number Of Units In Package 2	10
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	11.684 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information