Product datasheet

Specifications





Basic switch disconnector, ComPacT NS630bNA, fixed, electrically operated, 630A, 690VAC 50/60Hz, 3P

33440

① Discontinued

() Discontinued on: 01-Nov-2020

Main

Product Name	ComPacT NS new generation	
Device Short Name	Compact NS630b NA	
Product Or Component Type	Switch disconnector	
Device Application	Distribution	
Offer Type	C4	
Poles Description	3P	
Network Type	AC	
Performance Level	NA	
Suitability For Isolation	Yes conforming to IEC 60947-3	

Complementary

Network Frequency	50/60 Hz	
Control Type	Motor mechanism	
Mounting Mode	Fixed	
Mounting Support	Chassis	
[Ie] Rated Operational Current	AC-23A: 630 A AC 50/60 Hz 220/240 V AC-23A: 630 A AC 50/60 Hz 380/415 V	
	AC-23A: 630 A AC 50/60 Hz 440/480 V	
	AC-23A: 630 A AC 50/60 Hz 500/525 V	
	AC-23A: 630 A AC 50/60 Hz 660/690 V	
[Ui] Rated Insulation Voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3	
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947-3	
[Ith] Conventional Free Air Thermal Current	630 A at 60 °C	
[Icw] Rated Short-Time Withstand	25 kA during 0.5 s conforming to IEC 60947-3	
Current	4 kA during 20 s conforming to IEC 60947-3	
[Icm] Rated Short-Circuit Making Capacity	52 kA 690 V AC at 50/60 Hz	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz conforming to IEC 60947-3	
Contact Position Indicator	Yes	
Visible Break	No	
Mechanical Durability	6000 cycles conforming to IEC 60947-3	
Electrical Durability	rability 1000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3	
Connection Pitch	70 mm	

Height	327 mm
Width	210 mm
Depth	147 mm
Net Weight	14 kg

Environment

Standards	IEC 60947-3	
Product Certifications	ASTA ASEFA	
Pollution Degree	3 conforming to IEC 60947-3	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-5085 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	36.0 cm
Package 1 Width	23.0 cm
Package 1 Length	39.0 cm
Package 1 Weight	11.938 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information