# **Product datasheet**

Specifications





### circuit breaker Masterpact NW10H10 - 1000 A - 4 poles drawout

48736

#### Main

| Range                          | MasterPacT                       |
|--------------------------------|----------------------------------|
| Product Name                   | MasterPact NW                    |
| Circuit Breaker Name           | MasterPact NW10H10               |
| Product Or Component Type      | Circuit breaker                  |
| Device Application             | Power distribution protection    |
| Poles Description              | 4P                               |
| Neutral Position               | Left                             |
| Control Unit                   | Without control unit             |
| [In] Rated Current             | 1000 A at 40 °C                  |
| Performance Type               | H10 50 kA 1150 V AC              |
| [Ue] Rated Operational Voltage | 1150 V AC 50/60 Hz               |
| Suitability For Isolation      | Yes conforming to EN/IEC 60947-2 |
| Selectivity Category           | Category B                       |
| Control Type                   | Push-button                      |
| Mounting Mode                  | Drawout                          |

#### Complementary

| [Icu] Rated Ultimate Short-Circuit<br>Breaking Capacity | 50 kA at 1150 V AC 50/60 Hz  |
|---|------------------------------|
| [Ics] Rated Service Breaking<br>Capacity                | 50 kA at 1150 V AC 50/60 Hz  |
| [Icw] Rated Short-Time Withstand Current                | 50 kA 1 s<br>50 kA 3 s       |
| [Icm] Rated Short-Circuit Making<br>Capacity            | 105 kA 1150 V AC at 50/60 Hz |
| Sensor Rating   | 400 A<br>1000 A              |
| [Ui] Rated Insulation Voltage                           | 1250 V AC 50/60 Hz           |
| [Uimp] Rated Impulse Withstand<br>Voltage               | 12 kV                        |
| Maximum Breaking Time                                   | 25 ms                        |
| Maximum Closing Response Time                           | 70 ms                        |
| Mounting Support  | Backplate<br>Rails           |
| Upside Connection                                       | Rear                         |
| Downside Connection                                     | Rear                         |

| Connection Pitch       | 115 mm   |
|------------------------|--|
| Mechanical Durability  | 12500 cycles without maintenance<br>25000 cycles with maintenance              |
| Electrical Durability  | 500 cycles 1150 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 |
| Height                 | 439 mm   |
| Width                  | 556 mm   |
| Depth                  | 395 mm   |
| Net Weight             | 120 kg   |
| Standards              | EN/IEC 60947-1<br>EN/IEC 60947-2   |
| Product Certifications | CE<br>CCC<br>EAC   |

#### Environment

| Ip Degree Of Protection                  | IP30 conforming to IEC 60529                           |
|--|--|
| Pollution Degree                         | 3 conforming to IEC 60664-1                            |
| Ambient Air Temperature For<br>Operation | -2570 °C   |
| Ambient Air Temperature For<br>Storage   | -4085 °C   |
| Operating Altitude                       | 02000 m without derating<br>2000 m5000 m with derating |

## **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 0.1 cm  |
| Package 1 Width              | 0.1 cm  |
| Package 1 Length             | 0.2 cm  |
| Package 1 Weight             | 47.0 kg |

## **Contractual warranty**

Warranty

18 months

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information                       |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |