# **Product datasheet**

Specifications





# I/O module MES120G - Sepam series 60, 80 - 14 inputs+ 6 outputs 220...250V DC

59716

### Main

Module Type	Input/output module
Range Of Product	Sepam series 80 Sepam series 60
Device Short Name	MES120G

### Complementary

Input/Output Type	14 inputs + 6 outputs 220250 V at DC
Logic Input Number	14 220250 V 170275 V DC 3 mA 155 V enhanced
Number Of Outputs	1 control relay 5 annunciation relay
Output Type	<ul> <li>Annunciation relay</li> <li>Annunciation relay: 100240 V AC 47.563 Hz continuous current: 2 A breaking capacity: 0.001 kA cos φ &gt; 0.3</li> <li>Annunciation relay: 127 V DC continuous current: 2 A breaking capacity: 0.0005 kA L/R &lt; 20 ms</li> <li>Annunciation relay: 220 V DC continuous current: 2 A breaking capacity: 0.002 kA L/R &lt; 20 ms</li> <li>Annunciation relay: 24 V DC continuous current: 2 A breaking capacity: 0.002 kA L/R &lt; 20 ms</li> <li>Annunciation relay: 250 V DC continuous current: 2 A breaking capacity: 0.002 kA L/R &lt; 20 ms</li> <li>Annunciation relay: 48 V DC continuous current: 2 A breaking capacity: 0.001 kA L/R &lt; 20 ms</li> <li>Annunciation relay: 48 V DC continuous current: 2 A breaking capacity: 0.001 kA L/R &lt; 20 ms</li> <li>Control relay: 100240 V AC 47.563 Hz continuous current: 8 A breaking capacity: 0.005 kA cos φ &gt; 0.3 making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 100240 V AC 47.563 Hz continuous current: 8 A breaking capacity: 0.008 kA resistive making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 127 V DC continuous current: 8 A breaking capacity: 0.0002 kA L/R &lt; 40 ms making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 127 V DC continuous current: 8 A breaking capacity: 0.0005 kA L/R &lt; 20 ms</li> <li>Control relay: 217 V DC continuous current: 8 A breaking capacity: 0.0007 kA resistive making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.0001 kA L/R &lt; 40 ms making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.0003 kA resistive making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.0004 kA L/R &lt; 40 ms making capacity: &lt; 15 A for 200 ms</li> <li>Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.0004 kA L/R &lt; 20 ms making capacity: &lt; 15 A for 200 ms</li> <li>Control relay</li></ul>

Height	170 mm
Width	40 mm
Depth	120 mm
Net Weight	0.38 kg
Mechanical Robustness	Earthquakes in operation (level: 2) : 1 Gn (vertical axes) conforming to IEC 60255-21-3
	Earthquakes in operation (level: 2) : 2 Gn (horizontal axes) conforming to IEC 60255-21-3
	Jolts de-energized (level: 2) : 20 Gn/16 ms conforming to IEC 60255-21-2
	Shocks de-energized (level: 2) : 27 Gn/11 ms conforming to IEC 60255-21-2
	Shocks in operation (level: 2) : 10 Gn/11 ms conforming to IEC 60255-21-2
	Vibrations de-energized (level: 2) : 2 Gn, 10 Hz150 Hz conforming to IEC 60255-21-1
	Vibrations in operation (level: 2) : 1 Gn, 10 Hz150 Hz conforming to IEC 60255-21-1
	Vibrations in operation (level: Fc) : 2 Hz13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6
Auxiliary Connection Terminal	Screw-type connectors1 cable(s) 0.22.5 mm <sup>2</sup>
	Screw-type connectors1 cable(s) 1.5 mm <sup>2</sup>
	Screw-type connectors1 cable(s) 2.5 mm <sup>2</sup>
	Screw-type connectors2 cable(s) 0.21 mm <sup>2</sup>
	Screw-type connectors2 cable(s) 1 mm <sup>2</sup>

### Environment

Electromagnetic Compatibility	<ul> <li>1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 60255-22-1</li> <li>1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 2.5 kV DM, conforming to ANSI C37.90.1</li> <li>100 kHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 61000-4-12</li> <li>Conducted disturbance emission: (emission tests), conforming to IEC 60255-25</li> <li>Conducted disturbance emission: (emission tests), A, conforming to EN 55022</li> <li>Disturbing field emission: (emission tests), A, conforming to EN 55022</li> <li>Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 4 kV contact, conforming to ANSI C37.90.3</li> <li>Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 6 kV contact, conforming to IEC 60255-22-2</li> <li>Fast transient bursts: (immunity tests-conducted disturbances), 4 kV, 2.5 kHz, conforming to ANSI C37.90.3</li> <li>Electrostatic discharge: (immunity tests-conducted disturbances), 4 kV, 2.5 kHz, conforming to ANSI C37.90.1</li> <li>Fast transient bursts: (immunity tests-conducted disturbances), 4 kV, 2.5 kHz, conforming to IEC 60255-22-4</li> <li>Fast transient bursts: (immunity tests-conducted disturbances), IV, 4 kV, 2.5 kHz, conforming to IEC 61000-4-4</li> <li>Immunity to conducted RF disturbances: (immunity tests-conducted disturbances), III, 10 V, conforming to IEC 60255-22-3</li> <li>Immunity to radiated fields: (immunity tests-radiated disturbances), 10 V/m, 80 MHz 1 GHz, conforming to IEC 60255-22-3</li> <li>Immunity to radiated fields: (immunity tests-radiated disturbances), 35 V/m, 25 MHz 1 GHz, conforming to IEC 60255-22-3</li> <li>Immunity to radiated fields: (immunity tests-radiated disturbances), 10 V/m, 80 MHZ 1 GHz, conforming to IEC 60255-22-3</li> <li>Immunity to radiated fields: (immunity tests-radiated disturbances), 35 V/m, 25 MHz 1 GHz, conforming to IEC 60255-22-3</li> <li>Immunity to</li></ul>
	Voltage interruptions: (immunity tests-conducted disturbances), 100 % during 100 ms, conforming to IEC 60255-11

#### **Climatic Withstand**

Influence of corrosion/gaz test 2 (in operation) : 21 days, 75 % RH, 25 °C, 0.5 ppm H2S, 1 ppm S02 conforming to IEC 60068-2-60
Influence of corrosion/gaz test 4 (in operation) : 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm S02, 0.2 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60 Continuous exposure to damp heat (in operation) : Cab: 10 days, 93 % RH, 40 °C
conforming to IEC 60068-2-78 Continuous exposure to damp heat (in storage) : Cab: 56 days, 93 % RH, 40 °C conforming to IEC 60068-2-78
Continuous exposure to damp heat (in storage) : Db: 6 days, 95 % RH, 55 °C conforming to IEC 60068-2-30 Exposure to cold (in operation) : Ad: - 25 °C conforming to IEC 60068-2-1
Exposure to cold (in operation) : Ad: - 25 °C conforming to IEC 60068-2-1 Exposure to cold (in storage) : Ab: - 25 °C conforming to IEC 60068-2-1 Exposure to dry heat (in operation) : Bd: 70 °C conforming to IEC 60068-2-2
Exposure to dry heat (in storage) : Bb: 70 °C conforming to IEC 60068-2-2 Salt mist (in operation) : Kb/2: 6 days conforming to IEC 60068-2-52 Temperature variation with specified variation rate (in storage) : Nb: - 25 °C to 70 °C, 5 °C/min conforming to IEC 60068-2-14

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.7 cm
Package 1 Width	14.4 cm
Package 1 Length	21.0 cm
Package 1 Weight	555.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.263 kg

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Mercury Free

Rohs Exemption Information Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information