

# Product datasheet

Specifications



## Acti 9 Isolator xSW 2P 40A 1.25kA 240V AC

A9S2P040

### Main

Range of product	ISW 40...125
Range	Acti9
Product or component type	Isolator
Device application	Isolation

### Complementary

[Ie] rated operational current	40 A at 240 V AC
[Ui] rated insulation voltage	6 kV
[Uimp] rated impulse withstand voltage	500 V
Poles description	2P
Rated breaking capacity	1.25 kA
Short-circuit withstand	20 A
[Us] rated supply voltage	48 V DC 1P 100 V DC 2P
Utilisation category	AC-22
Total number of 18 mm modules	2
Product destination	Distribution board

### Environment

Ambient air temperature for operation	-20...50 °C
Pollution degree	3
Standards	IEC 60669-1 IEC 60947-3

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	7.0 cm
Package 1 Length	8.0 cm

---

Package 1 Weight 0.17 kg

## Offer Sustainability

---

REACH Regulation [REACH Declaration](#)

---

REACH free of SVHC Yes

---

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

---

Toxic heavy metal free Yes

---

Mercury free Yes

---

RoHS exemption information [Yes](#)

---

China RoHS Regulation [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

Recommended replacement(s)