# **Product datasheet**

Specifications



# TeSys D thermal overload relays remote electrical tripping - 24 V DC/ AC

LA7D03B

### Main

Range	TeSys	
Product Or Component Type	Electrical remote tripping	
Device Short Name	LA7D	
Accessory / Separate Part Category	Electrical accessory	
Product Compatibility	LRD15	
	LR2D	
	LR3D15	
	LR3D35	
	LR3D33	
	LRD33	
	LRD43	
	LR3D43	
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz	
	24 V DC	

## Complementary

Maximum Inrush Power In Va	100 VA
Inrush Power In W	0100 W
Net Weight	0.09 kg

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	4.8 cm
Package 1 Length	4.8 cm
Package 1 Weight	109.0 g
Unit Type Of Package 2	S01
Number Of Units In Package 2	32
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.668 kg

### **Contractual warranty**

Warranty

18 months

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

	Reach Free Of Svhc	
0	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Compliant
		EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration
		Pro-active China RoHS declaration (out of China RoHS legal scope)
Wee	e	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins