Product datasheet

Specification





Easy TeSys differential thermal overload relay 1.6...2.5 A - class 10A

LRE07

Main

| Range | Easy TeSys | |
|---------------------------|--|--|
| Range Of Product | Easy TeSys Protect | |
| Product Or Component Type | Differential thermal overload relay | |
| Device Short Name | LRE | |
| Relay Application | Motor protection | |
| Phase Failure Sensitivity | Tripping current 130 % of Ir on two phase, the last one at 0 conforming to IEC 60947-4-1 | |
| Colour | Grev (RAL 7011) | |

Complementary

| Product Compatibility | LC1E0638 |
|--|--|
| Network Type | AC |
| Network Frequency | 5060 Hz |
| Mounting Support | Under contactor Plate, with specific accessories Rail, with specific accessories |
| Thermal Overload Class | Class 10A conforming to IEC 60947-4-1 |
| Signalling Function | Relay trip indicator |
| Thermal Protection Adjustment Range | 1.62.5 A |
| Tripping Threshold | 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1 |
| Mechanical Robustness | Shocks: 6 Gn for 11 ms conforming to IEC 60068-2-7 Vibrations: 3 GN conforming to IEC 60068-2-6 |
| Auxiliary Contact Composition | 1 NO + 1 NC |
| [Ith] Conventional Free Air Thermal Current | 5 A for signalling circuit |
| [Ue] Rated Operational Voltage | <= 690 V AC |
| Associated Fuse Rating | 6 A gG for power circuit 4 A aM for power circuit 5 A gG for signalling circuit |
| [Ui] Rated Insulation Voltage | 690 V conforming to IEC 60947-4-1 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV |
| Local Signalling | Trip indicator |
| Control Type | Push-button red stop: Push-button green reset: |
| Temperature Compensation | -2060 °C |

| Connections - Terminals | Power circuit: screw clamp terminals 1 1.56 mm² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end | |
|-------------------------------|--|--|
| | | |
| | Power circuit: screw clamp terminals 1 16 mm² - cable stiffness: solid without cable end | |
| | Signalling circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible without cable end | |
| | Signalling circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end | |
| | Signalling circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: solid without cable end | |
| Recommended Tightening Torque | Power circuit: 1.7 N.m - on screw clamp terminals Signalling circuit: 1.7 N.m - on screw clamp terminals | |
| Height | 44.5 mm | |
| Width | 45 mm | |
| Depth | 70 mm | |
| Net Weight | 0.13 kg | |

Environment

| Standards | IEC 60947-5-1 IEC 60947-4-1 | |
|---------------------------------------|--|--|
| Product Certifications | EAC | |
| Protective Treatment | TH conforming to IEC 60068 | |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 | |
| Ambient Air Temperature For Operation | -2060 °C without derating conforming to IEC 60947-4-1 -2070 °C with derating | |
| Ambient Air Temperature For Storage | -6080 °C | |
| Fire Resistance | 850 °C conforming to IEC 60068-2-1 | |
| Dielectric Strength | 6 kV at 50 Hz conforming to IEC 60255-5 | |
| Electromagnetic Compatibility | Surge withstand: 6 kV conforming to IEC 60801-5 | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|--------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.5 cm |
| Package 1 Width | 8 cm |
| Package 1 Length | 8.5 cm |
| Package 1 Weight | 143 g |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 33 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 5.1 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |