



circuit breaker Compact NSXm N (50 kA at 415 VAC), 3P, 63 A rating TMD trip unit, compression lugs and busbar connectors

LV426455

! Discontinued on: 31-Dec-2022

#### Main

| Range   | ComPact   |
|---|---|
| Product Name  | ComPact NSXm  |
| Range Of Product  | ComPact NSXm  |
| Device Short Name                                       | NSXm 63N  |
| Product Or Component Type                               | Circuit breaker   |
| Device Application                                      | Protection<br>Distribution  |
| Number Of Poles   | 3P  |
| Protected Poles Description                             | 3D  |
| [In] Rated Current                                      | 63 A at 40 °C   |
| [Ue] Rated Operational Voltage                          | 690 V AC 50/60 Hz   |
| Network Type  | AC  |
| Network Frequency                                       | 50/60 Hz  |
| Suitability For Isolation                               | Yes conforming to EN/IEC 60947-2  |
| Utilisation Category                                    | Category A  |
| [Icu] Rated Ultimate Short-Circuit<br>Breaking Capacity | 90 kA Icu at 220240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 380415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>25 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>15 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 600690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance Level                                       | N 50 kA 415 V AC  |
| Trip Unit Name  | TM-D  |
| Trip Unit Technology                                    | Thermal-magnetic  |
| Trip Unit Protection Functions                          | LI  |
| Control Type  | Toggle  |
| Circuit Breaker Mounting Mode                           | By screws<br>Clip-on  |

# Complementary

| [Ui] Rated Insulation Voltage          | 800 V AC 50/60 Hz |
|--|-------------------|
| [Uimp] Rated Impulse Withstand Voltage | 8 kV              |

| [Ics] Rated Service Short-Circuit                         | 90 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2  |
|---|--|
| Breaking Capacity   | 50 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2  |
| 99  | S Comment of the comm |
|   | 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2   |
|   | 25 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2   |
|   | 15 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2   |
|   | 2.5 kA at 660690 V AC 50/60 Hz conforming to IEC 60947-2   |
| Mechanical Durability                                     | 20000 cycles   |
| Electrical Durability                                     | 10000 cycles at 440 V In   |
|   | 20000 cycles at 440 V In/2   |
|   | 5000 cycles at 690 V In  |
|   | 10000 cycles at 690 V In/2   |
| Mounting Support  | Plate  |
| meaning cappoin   |  |
|   | DIN rail   |
| Connection Terminals                                      | compression lug/busbar   |
| Connection Pitch  | 35 mm with spreaders   |
|   | 27 mm without spreaders  |
| 9 Mm Pitches  | 9 module   |
| Protection Type   | L : for overload protection (thermal)  |
|   | I : for short-circuit protection (magnetic)  |
| Trip Unit Rating  | 63 A at 40 °C  |
| Long-Time Pick-Up Adjustment Type Ir (Thermal Protection) | Adjustable   |
| · · · · · · · · · · · · · · · · · · ·                     |  |
| [Ir] Long-Time Protection Pick-Up<br>Adjustment Range     | 0.71 x ln  |
| Long-Time Protection Delay<br>Adjustment Type Tr          | Fixed  |
| [Im] Magnetic Protection Pick-Up Range                    | 800 A  |
| Earth-Leakage Protection                                  | Without  |
| Number Of Slots For Electrical                            | 1 slot(s) for auxiliary switch OF  |
| Auxiliaries   | 1 slot(s) for alarm switch SD  |
|   | 1 slot(s) for voltage release MN or MX   |
| Width (W)   | 81 mm  |
| Height (H)  | 137 mm   |
| Depth (D)   | 80 mm  |
| Net Weight  | 1.06 kg  |
| Colour  | Grey (RAL 7016)  |
|   |  |

## **Environment**

| Standards                             | EN/IEC 60947                                      |
|---------------------------------------|---|
| Product Certifications                | CCC<br>EAC<br>Marine                              |
| Pollution Degree                      | 3 conforming to IEC 60664-1                       |
| Ip Degree Of Protection               | IP40 conforming to IEC 60529                      |
| Ik Degree Of Protection               | IK07 conforming to IEC 62262                      |
| Ambient Air Temperature For Operation | -2570 °C  |
| Ambient Air Temperature For Storage   | -5085 °C  |
| Relative Humidity                     | 095 %   |
| Operating Altitude                    | 02000 m without derating 20005000 m with derating |

# **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 9.0 cm   |
| Package 1 Width              | 12.5 cm  |
| Package 1 Length             | 21.5 cm  |
| Package 1 Weight             | 1.3 kg   |
| Unit Type Of Package 2       | S03      |
| Number Of Units In Package 2 | 9        |
| Package 2 Height             | 30.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 12.29 kg |

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information                         |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |

25-Apr-2024