Product datasheet





Lexium 62 Double Drive 15 A accessory kit included

LXM62DD15D21000

Main

Range Of Product	PacDrive 3	
Product Or Component Type	Double drive	
Device Short Name	LXM 62	

Complementary

o o in promontary	
Product Compatibility	Servo motor SHS Servo motor SH3 (70 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor SH3 (70 mm, 3 motor stacks)optimized in terms of torque and speed Servo motor SH3 (100 mm, 1 motor stacks)optimized in terms of torque and speed Servo motor SH3 (100 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor SH3 (100 mm, 2 motor stacks)optimized in terms of high torque Servo motor SH3 (100 mm, 3 motor stacks)optimized in terms of high torque Servo motor SH3 (140 mm, 1 motor stacks)optimized in terms of high torque Servo motor MH3 (70 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor MH3 (70 mm, 3 motor stacks)optimized in terms of torque and speed Servo motor MH3 (100 mm, 1 motor stacks)optimized in terms of torque and speed
Network Number Of Phases	Three phase
[Us] Rated Supply Voltage (Through Power Supply Module)	400 V (- 1010 %) for three phase 230 V (- 1010 %) for three phase 230 V (- 1010 %) for single phase
Supply Frequency	50/60 Hz - 55 %
Continuous Output Current	5 A at 4 kHz
Output Current 3S Peak	15 A at 4 kHz
Continuous Power	2.4 kW
Nominal Power	2.4 kW
Switching Frequency	8 kHz
Overvoltage Category	III
Electrical Connection	Terminal, clamping capacity: 0.215 mm², AWG 24AWG 16 (CN4) Terminal, clamping capacity: 0.516 mm², AWG 20AWG 6 (CN5) Terminal, clamping capacity: 0.7516 mm², AWG 18AWG 6 (CN6) Terminal, clamping capacity: 0.26 mm², AWG 24AWG 10 (CN7)
Tightening Torque	CN1: 2.5 N.m
Number Of Inputs	2 digital 2 touch probe
Discrete Input Voltage	24 V DC for - 2025 %
Number Of Outputs	2 digital
Discrete Output Voltage	24 V DC
Safety Function	STO (safe torque off)
Communication Interface	SERCOS III, integrated

Life Is On Schneider 25-Apr-2024

Depth	270 mm
Height	310 mm
Width	44.5 mm
Net Weight	3 kg

Environment

Standards	IEC 61508 ISO 13849-1 IEC 61800-5-1 IEC 62061 IEC 62061 CSA C22.2 No 14 IEC 61800-5-2 ISO 13849-2 UL 508C IEC 61800-3	
Product Certifications	UL EAC CSA CE TÜV	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Vibration Resistance	10 m/s ² conforming to IEC 60721-3-3	
Shock Resistance	100 m/s² conforming to IEC 60721-3-3	
Pollution Degree	2 conforming to IEC 61800-5-2	
Environmental Characteristic	3K3 conforming to IEC 60721-3-3	
Relative Humidity	585 %	
Ambient Air Temperature For Operation	555 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	32.5 cm
Package 1 Length	42.5 cm
Package 1 Weight	4.01 kg
Unit Type Of Package 2	S06
Number Of Units In Package 2	10
Package 2 Height	75.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	53.1 kg



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
②	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information