Product datasheet

Specifications





current transformer tropicalised DIN mount 250 5 for cables d. 21

METSECT5CC025

Main

Range	PowerLogic
Product Name	СТ
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 5 VA
	Class 1 at 6 VA
	Class 3 at 7 VA
[In] Rated Current	250 A

Complementary

Tropicalised for cable
250/5
15 kA
2.5 lth
5
< 720 V AC 50/60 Hz
3 kV
By screws Clip-on
Mounting plate DIN rail
44 mm outside:
65 mm outside:
30 mm frame: 37 mm total:
21 mm
0.175 kg
3 kV
Class B
21 mm
With

Environment

Standards	VDE 0414 IEC 61869-2
Product Certifications	CE
Ip Degree Of Protection	IP20
Relative Humidity	095 %
Ambient Air Temperature For Operation	-2560 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	5.5 cm
Package 1 Length	8.2 cm
Package 1 Weight	182.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	50
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.31 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins