Product datasheet





EasyLogic PM2210, Power & Energy meter, Total Harmonic, LCD, Pulse, class 1

METSEPM2210D

Main

wain	
Range	EasyLogic
Product Name	EasyLogic PM2200
Device Short Name	PM2210
Product Or Component Type	Power meter
Complementary	
Device Application	Power monitoring Sub billing
•	

Power Quality Analysis	total harmonic distortion
Type Of Measurement	Apparent power min/max, total
	Active and reactive power min/max, total
	Current min/max, avg
	Voltage min/max, avg
	Frequency min/max, avg
	Total current harmonic distortion THD (I) per phase
	Total voltage harmonic distortion THD (U) per phase
	Power factor min/max, avg
	Apparent energy total
	Active and reactive energy total
Metering Type	Active, reactive, apparent energy (signed, four quadrant)
	Calculated neutral current
	Current I, I1, I2, I3
	Active power P, P1, P2, P3
	Reactive power Q, Q1, Q2, Q3
	Unbalance current
	Voltage U, U21, U32, U13, V, V1, V2, V3
	Peak demand currents
	Demand power P, Q, S
	Apparent power S, S1, S2, S3
	Peak demand power PM, QM, SM
Accuracy Class	Class 1 active energy conforming to IEC 62053-21
	Class 1 reactive energy conforming to IEC 62053-24
Measurement Accuracy	Apparent power +/- 1 %
	Active energy +/- 1 %
	Reactive energy +/- 1 %
	Active power +/- 1 %
	Voltage +/- 0.5 %
	Power factor +/- 0.01
	Current +/- 0.5 %
	Frequency +/- 0.05 %
Measurement Current	56000 mA

35...480 V AC 50/60 Hz between phases 20...277 V AC 50/60 Hz between phase and neutral 480...999000 V AC 50/60 Hz with external VT

45...65 Hz

Measurement Voltage

Frequency Measurement Range

[Us] Rated Supply Voltage	44277 V AC 4565 Hz +/- 10 % 44277 V DC +/- 10 %	
Network Frequency	50 Hz 60 Hz	
Ride-Through Time	100 ms 120 V AC typical 400 ms 230 V AC typical 50 ms 125 V DC typical	
[In] Rated Current	1 A 5 A	
Maximum Power Consumption In Va	6 VA at 277 V AC	
Maximum Power Consumption In W	3.3 W (power lines (AC)) 2 W at 277 V (power lines (DC))	
Input Impedance	Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)	
Tamperproof Of Settings	Protected by access code	
Display Type	Backlit LCD	
Display Colour	Monochrome	
Display Resolution	128 x 128 pixels	
Demand Intervals	Configurable from 1 to 60 min	
Information Displayed	Demand current (past value) Demand current (present value) Demand power (past value) Demand power (present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude	
Control Type	4 x button	
Local Signalling	Red LED: output signal 19999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED: module operating (RUN)	
Number Of Inputs	0	
Number Of Outputs	1 pulse	
Pop Parameter	Pulse: 20 ms (540 V DC, 20 mA max)19999000 pulse/ k_h (kWh, kVAh, kVARh)	
Impulse Duration	20 ms	
Communication Port Protocol	POP	
Sampling Rate	64 samples/cycle	
Cybersecurity	Enable/disable communication ports	
Communication Service	Remote monitoring	
Language	Portuguese Spanish Russian Chinese German English French	

Product Certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 RCM EAC C-Tick	
Mounting Mode	Clip-on	
Mounting Position	Vertical	
Mounting Support	Framework	
Provided Equipment	1 x installation guide	
Measurement Category	Category III 480 V Category II 480600 V	
Electrical Insulation Class	Class II Double insulation	
Flame Retardance	V-0 conforming to UL 94	
Connections - Terminals	Current transformer: screw connection (bottom) 6 Voltage inputs: screw connection (top) 4	
Material	Polycarbonate	
Width	96 mm	
Depth	76.09 mm total: 61.64 mm embedded:	
Height	96 mm	
Net Weight	300 g	
Targeted Country	India	

Environment

Service Life	7 year(s)	
Ip Degree Of Protection	IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529	
Relative Humidity	595 % at 50 °C	
Pollution Degree	2	
Ambient Air Temperature For Operation	-1060 °C	
Ambient Air Temperature For Storage	-2570 °C	
Operating Altitude	<= 2000 m	
Electromagnetic Compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A	
Overvoltage Category	III	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	9.6 cm

Package 1 Length	9.6 cm	
Package 1 Weight	0.5 kg	



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information