# **Product datasheet**

Specification





Slim interface relay preassembled, 6 A, 1 CO, LED, protection module, screw connector, 230 V AC

RSL1PVPU

### Main

Range Of Product	Harmony Electromechanical Relays
Series Name	Interface relay
Product Or Component Type	Pre-assembled plug-in relay with socket
Device Short Name	RSL
Contacts Type And Composition	1 C/O
Contact Operation	Standard
[Uc] Control Circuit Voltage	230 V AC/DC
[Ithe] Conventional Enclosed Thermal Current	6 A at -4055 °C
Status Led	With
Shape Of Pin	Flat (PCB type)

## Complementary

Fixing Mode	Plastic compression spring
Average Resistance	20500 Ohm network: DC at 23 °C +/- 10 %
[Ui] Rated Insulation Voltage	250 V conforming to IEC 277 V conforming to cUL
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC
Contacts Material	Silver alloy (AgSnO2)
[le] Rated Operational Current	6 A 1 C/O (AC-1/DC-1) conforming to IEC/UL
Minimum Switching Current	100 mA
Maximum Switching Voltage	277 V
Minimum Switching Voltage	12 V
Maximum Switching Capacity	1500 VA 150 W
Minimum Switching Capacity	120 mW
Operating Rate	<= 72000 cycles/hour no-load <= 360 cycles/hour under load
Mechanical Durability	10000000 cycles
Electrical Durability	60000 cycles for resistive load, 6 A at 250 V, AC-1
Operating Time	5 ms reset 12 ms
Reset Time	20 ms
Marking	CE

RT III
Level A group mounting
Any position
78.6 mm
6.2 mm
95 mm
(11-12-14)OC (A1-A2)CO
10
0.029 kg
6 A at 250 V AC 0.5 mm mounting distance
0.17 W, DC
>= 0.05 Uc
Separate
Screw connectors, 1 x 0.21 x 2.5 mm² (AWG 24AWG 14) flexible with cable end Screw connectors, 1 x 0.21 x 2.5 mm² (AWG 24AWG 14) solid without cable end
< 0.5 N.m for M2.5 screw(s)
B10d = 60000
Without push-button
35 mm symmetrical DIN rail
Complete product
230 V AC/DC (input voltage limit: 184264.5 V)
1000 V AC between contacts

Input Voltage	230 V AC/DC (input voltage limit: 184264.5 V)
Dielectric Strength	1000 V AC between contacts
	4000 V AC between coil and contact
Standards	IEC 61810-1
	UL 508
	CSA C22.2 No 14
Product Certifications	GOST
	CSA
	UL
Ambient Air Temperature For Storage	-4085 °C
Vibration Resistance	10 gn, amplitude = +/- 1 mm (f = 10150 Hz)10 cycles not operating conforming to IEC 60068-2-6
	5 gn, amplitude = +/- 1 mm (f = 10150 Hz)10 cycles in operation conforming to IEC 60068-2-6
Ip Degree Of Protection	IP40 conforming to IEC 60529
Shock Resistance	10 gn (duration = 11 ms) for in operation conforming to IEC 60068-2-27
	5 gn (duration = 11 ms) for not operating conforming to IEC 60068-2-27
Ambient Air Temperature For Operation	-4070 °C

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.7 cm

Package 1 Width	9.6 cm
Package 1 Length	7.9 cm
Package 1 Weight	28.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	7.0 cm
Package 2 Width	10.3 cm
Package 2 Length	8.5 cm
Package 2 Weight	311.0 g
Unit Type Of Package 3	S03
Number Of Units In Package 3	300
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	9.822 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Reach Free Of Svhc
<b>⊘</b>	Toxic Heavy Metal Free
<b>9</b>	Mercury Free
<b>9</b>	Rohs Exemption Information Yes
<b>⊘</b>	Toxic Free
<b>⊘</b>	Phenolic Free Solution

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

## **RSL1PVPU**

## **Dimensions Drawings**

#### **Dimensions**

