# **Product datasheet**

Specifications





# Solid state modular relay, 6 A, DC swtching, input 4...32 V DC, output 1...60 V DC

SSM1D26BD

#### Main

Range Of Product	Harmony Solid State Relays
Product Or Component Type	Solid state relay up to 10 A
Device Short Name	SSM
Number Of Channels	1
Number Of Phases	1 phase
Output Switching Mode	DC switching

## Complementary

Complementary	
Mounting Support	Symmetrical DIN rail
[In] Rated Current	6 A
Output Voltage	160 V DC
[Uc] Control Circuit Voltage	432 V DC
Tightening Torque	0.50.8 N.m for input 0.50.8 N.m for output
Connections - Terminals	Screw terminals: 1 x 0.31 x 1.5 mm², (AWG 22AWG 16) for input Screw terminals: 1 x 0.31 x 2.5 mm², (AWG 22AWG 14) for output
Maximum Capacitance	10 pF for input/output
Insulation Resistance	1000 MOhm at 500 V DC
Local Signalling	LED (green) for input status
Minimum Switching Voltage	4 V DC turn-on
Maximum Switching Voltage	1 V DC turn-off
Input Current	811 mA
Solid State Output Type	Mosfet output DC switching
Load Current	0.00256 A
Transient Overvoltage	60 V
Surge Current	60 A for 10 ms
Maximum Voltage Drop	<0.6 V on-state
Resistance	0.1 Ohm on-state
Maximum Leakage Current	0.1 mA off-state
Response Time	0.6 ms (turn-on) 0.3 ms (turn-off)
Overvoltage Category	III

Width	11 mm
Height	90.3 mm
Depth	83.7 mm
Net Weight	0.05 kg

# **Environment**

Flame Retardance	V0 conforming to UL 94
Dielectric Strength	4 kV DC for input/output 4 kV DC for input or output to case
Pollution Degree	2
Standards	IEC 61000 IEC 62314 IEC 60950-1
Product Certifications	UL CSA
Marking	CE
Ip Degree Of Protection	IP20
Ambient Air Temperature For Operation	-3080 °C
Ambient Air Temperature For Storage	-30100 °C

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2 cm
Package 1 Width	9 cm
Package 1 Length	9 cm
Package 1 Weight	61 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	96
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.26 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance



Mercury Free



Rohs Exemption Information

Yes


#### **Certifications & Standards**


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

# SSM1D26BD

#### **Dimensions Drawings**

#### **Dimensions**






# **Product datasheet**

## SSM1D26BD

#### Performance Curves

#### **Derating Curves**



- A : Load Current (Amperes)
- B : Ambient Temperature (°C)
- 1 : Multiple units, no minimum spacing between components
- 2: Installed single unit, distance to adjacent components more than 11 mm