Product datasheet

Specifications





safety controller XPS-MC - 24 V DC - 16 input - 32 LEDs signalling

XPSMC16ZP

(!) Discontinued

Main

Range Of Product	Preventa Safety automation	
Product Or Component Type	Configurable safety controller	
Safety Module Name	XPSMC	
Safety Use Category	Category 4 maximum conforming to EN 954-1/EN/ISO 13849-1 PLE maximum conforming to ISO 13849-1 SIL 3 maximum conforming to IEC 61508	
Type Of Start	Configurable	
Standards	EN 1760-1/ISO 13856-1 EN 574/ISO 13851 IEC 60947-5-1 IEC 61508 IEC 60204-1 EN 954-1/EN/ISO 13849-1 IEC 61496-1	
Product Certifications	UL CSA TÜV	
[Us] Rated Supply Voltage	24 V DC - 2020 %	
Number Of Inputs	16	
Communication Port Protocol	Modbus with 1 RJ45 port(s), serial link, transmission rate: 1200 bps, 2400 bps, 4800 bps, 9600 bps or 19200 bps Profibus with 1 SUB-D 9-pin female port(s), serial link, transmission rate: 12 Mbps	
Safety Level	Can reach PL e/category 4 conforming to EN 954-1/EN/ISO 13849-1 Can reach SIL 3 conforming to IEC 61508	

Complementary

Function Of Module	Dynamic monitoring of hydraulic valves on linear presses Eccentric press
	Emergency stop monitoring, with or without time delay, 1 or 2-channel wiring
	Enabling switch monitoring, 2 or 3 contacts
	Foot switch monitoring
	Guard monitoring for injection presses and blowing machines
	Guard monitoring with 1 or 2 limit switches
	Hydraulic press
	Magnetic switch monitoring category 4 conforming to EN/IEC 61496
	Monitoring safety stop at top dead centre on eccentric press category 3 conforming
	to EN 574/ISO 13851
	Muting function of light curtains
	Position selector
	Safety mat monitoring
	Safety time delays
	Shaft/chain breaking monitor
	Zero speed detection
	Light curtain monitoring category 4 conforming to IEC 61496

19-Apr-2024 Life Is On Schneider

Two-hand control category 3 conforming to EN 574/ISO 13851

Synchronisation Time Between Inputs	Depending on configuration selected
Power Consumption In W	12 W
Input Protection Type	External fuse 16 A
[Uc] Control Circuit Voltage	28.8 V
Maximum Line Resistance	100 Ohm <2000 m
Output Type	2 relays, 2 NO contacts (4 NO total) circuit(s) Solid state, 6 circuit(s), volt-free
Breaking Capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output
Breaking Capacity	2 A at 24 V for static output circuit 1.5 A at 24 V (DC-13) time constant: 50 ms for relay output
Output Thermal Current	4 A for both outputs simultaneously 6 A for 1 output and 2 A for the other for relay output
[Ith] Conventional Free Air Thermal Current	16 A for relay output 6.5 A for static output circuit
Associated Fuse Rating	16 A gL for power supply 4 A gL for relay output 6 A fast blow for relay output
Minimum Output Current	10 mA for relay output
Minimum Output Voltage	17 V for relay output
Response Time	Configurable : 20 ms or 30 ms with software XPSMCWIN
[Ui] Rated Insulation Voltage	300 V (pollution degree 2) conforming to IEC 60647-5-1, DIN VDE 0110 part 1
[Uimp] Rated Impulse Withstand Voltage	4 kV overvoltage category III conforming to IEC 60647-5-1, DIN VDE 0110 part 1
Method Of Access	Slave
Exchange Size	14 words
Number Of Addresses	1125 for Profibus 1247 for Modbus
Parity	Even for Modbus No for Modbus Odd for Modbus
Data Format	1 start bit/8 data bits 1 stop bit even or odd 2 stop bits without parity RTU (Remote Terminal Unit) mode
Supported Modbus Function	01: 8-bit output data/32-bit input data 02: 32-bit input data/8-bit output data 03: information and errors
Local Signalling	32 LEDs
Mounting Support	Mounting plate
Depth	153 mm
Height	151.5 mm
Width	74 mm
Net Weight	0.82 kg

Environment

Ip Degree Of Protection	IP20 conforming to IEC 60529
Ambient Air Temperature For Operation	-1055 °C
Ambient Air Temperature For Storage	-2585 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	18.000 cm
Package 1 Length	26.000 cm
Package 1 Weight	1.270 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	8.430 kg

Contractual warranty

19-Apr-2024

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance


	Mercury Free	
⊘	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Environmental Disclosure	Product Environmental Profile
Environmental Disclosure Weee	The product must be disposed on European Union markets following specific waste
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
	·

Dimensions Drawings


Dimensions



When using XPSMCTS• connectors this dimension is 153 mm (6.02 in)
When using XPSMCTC• connectors this dimension is 151,5 mm (5.96 in)

Mounting and Clearance

Installation



Metal adaptor for fixing on metal: DIN rail 35 mm/1.38 in.

XPSMC16ZP

Connections and Schema


Wiring Diagrams

Refer to the Instruction Sheet

To download the instruction sheet, follow below procedure:



XPSAC5121
module XPSAC - Emergency stop - 24 V AC DC
Download XPSAC5121 product datasheet




- 1 Click on Download & Documents.
- 2 Click on Instruction sheet.

XPSMC16ZP

Technical Description

Safety Functions



Product datasheet

XPSMC16ZP

	• Sensing mat monitoring.
7	 Light curtains monitoring: Relay output type. Solid-state output type. "Muting" function for light curtains.
	Zero speed detection.
	 Dynamic monitoring of hydraulic valves on linear presses.
	• Safety time delays.
	Monitoring safety stop at top dead centre on eccentric press. Hydraulic press. Eccentric press.

Product datasheet

XPSMC16ZP



- Enabling switching monitoring:
 - 2 contact type.3 contact type.

Other functions:

- Foot switch monitoring
- Chain shaft breakage monitoring
- Position selector