Product datasheet

Specifications



① Discontinued

ION7550 - wDispl - 5MB 256s - 5A 240VAC/300VDC 50Hz - RS+T2+E - 8I+3R+4O

M7550A0C0B5E0A0A

Discontinued on: 1 Nov 2020

Main

Range	PowerLogic
Device Short Name	ION7550
Product Or Component Type	Energy and power quality meter

Complementary

Complementary	
Power Quality Analysis	harmonic distortion voltage sag and swell detection waveform capture compliance monitoring dip and swell, transient disturbance direction detection programmablity (logic and math functions) setpoint learning up to the 63rd harmonic
Device Application	Co-generation and IPP monitoring Instrument transformer correction Load curtailment Energy pulsing and totalisation Demand and power factor control Equipment monitoring and control Tariff metering
Type Of Measurement	Current Voltage Frequency Apparent power total Power factor total Apparent power per phase Power factor per phase Active power total Active power per phase Reactive power total Reactive power per phase
Supply Voltage	110300 V DC 85240 V AC 4763 Hz
Network Frequency	50 Hz
[In] Rated Current	5 A
Type Of Network	1P + N 3P + N 3P
Power Consumption In Va	20 VA at 85240 V AC 20 VA at 110300 V DC
Maximum Power Consumption In Va	45 VA at 85240 V AC 45 VA at 110300 V DC
Display Resolution	320 x 240 pixels QVGA

Display Type	Backlit LCD
Sampling Rate	256 samples/cycle
Measurement Current	05 A
Input Type	Current 0.00520 A (impedance 0.002 Ohm)
Measurement Voltage	100600 V AC phase to phase 57347 V AC phase to neutral
Frequency Measurement Range	4269 Hz
Number Of Inputs	8 digital 120 V DC
Measurement Accuracy	Current 0.1 % 15 A Voltage 0.1 % 57288 V Energy 0.2 %
Accuracy Class	Class 0.2S energy conforming to IEC 62053-22
Number Of Outputs	3 relay 4 solid state
Communication Port Protocol	Telnet DNP3 at <= 115.2 kbits/s ION at <= 115.2 kbits/s Modbus at <= 115.2 kbits/s IEC 61850 TCP/IP at 10/100 Mbit/s
Communication Port Support	RJ45: ETHERNET SUB-D 9: RS485/RS232 Terminal block: RS485 Infrared
Data Recording	Time stamping Sequence of event recording Data logs Event logs GPS synchronisation Min/max of instantaneous values Trending/forecasting
Transmission Rate	10/100 Mbit/s 30057600 bauds 300115200 bauds <= 19200 bauds
Memory Capacity	5 MB
Web Services	Web server
Tamperproof Of Settings	Protected by access code
Compatibility Code	ION7550
Environment	

Electromagnetic Compatibility	Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Electrostatic discharge conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields conforming to IEC 61000-4-3 1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5 Conducted and radiated emissions B conforming to CISPR 22
Mounting Mode	Flush-mounted
Mounting Support	Enclosure door
Type Of Installation	Indoor installation
Overvoltage Category	Ш
Ip Degree Of Protection	IP30 back: conforming to IEC 60529 IP50 front face: conforming to IEC 60529
Relative Humidity	595 %
Pollution Degree	2

Ambient Air Temperature For Operation	-2070 °C
Ambient Air Temperature For Storage	-4085 °C
Operating Altitude	02000 m
Standards	IEC 61010-1
Width	192 mm
Depth	174 mm
Height	192 mm
Net Weight	1.9 kg

Packing Units

Unit Type Of Package 1	DOF
Onit Type Of Fackage 1	PCE
Number Of Units In Package 1	1
Package 1 Height	26 cm
Package 1 Width	28 cm
Package 1 Length	44 cm
Package 1 Weight	3.5 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

4