Specifications



All In One Module 40kW 5rack InRow DX 208V

PFMIEC040D1N05D

Overview

Lead Time

Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Rated Power In W	40000 W
Number Of Rack Unit	42U
Battery Type	VRLA
Provided Equipment	EcoStruxure IT ready (UPS)

Batteries & Runtime

Number Of Battery Free Slots	0
Number Of Battery Filled Slots	0
Battery Power In Vah	0 VAh

General

Cooling	Option
---------	--------

Air-cooled split-system

Physical

Colour	White
Height	300 cm
Width	350.5 cm
Depth	762 cm
Net Weight	10000 kg
Mounting Mode	Not rack-mountable
Number Of Racks	5
Number Of Rack Free Space	210

Output

Power Per Rack	8 kW
Pdu Type	Metered
Maximum Configurable Power In W	40000 W

Minimum Configurable Power In 40000 W W

Conformance

Product Certifications UL listed
Environmental
Ambient Air Temperature For -24...55 °C
Operation

Operating Altitude 0...10000 ft

Communications & Management

Optional

Emergency Power Off

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	300 cm
Package 1 Width	762 cm
Package 1 Length	350.5 cm
Package 1 Weight	7000 kg

Contractual warranty

Warranty

1 year (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope