Specifications





Harmony XB7, Monolithic pilot light, plastic, yellow, Ø22, plain lens for BA9s bulb, <= 250 V

XB7EV65P

### Price: 7,371.82 NGN

#### Main

| Range Of Product                | Harmony XB7                      |
|---------------------------------|----------------------------------|
| Product Or Component Type       | Pilot light                      |
| Device Short Name               | XB7                              |
| Mounting Diameter               | 22 mm                            |
| Sale Per Indivisible Quantity   | 10                               |
| Operator Additional Information | With plain lens                  |
| Light Source                    | Incandescent (bulb not included) |
| Device Presentation             | Monolithic product               |

### Complementary

| Height                                    | 29 mm   |
|---|---|
| Width                                     | 29 mm   |
| Depth                                     | 54 mm   |
| Terminals Description Iso N°1             | (X1-X2)PL   |
| Net Weight                                | 0.018 kg  |
| Overvoltage Category                      | Class II conforming to IEC 60536  |
| Device Mounting                           | Fixing hole - diameter: 22.5 mm 22.3 +0.4/0 conforming to IEC 60947-5-1   |
| Fixing Center                             | >= 30 x 40 mm (support panel) metal - thickness: 16 mm<br>>= 30 x 40 mm (support panel) plastic - thickness: 26 mm  |
| Fixing Mode                               | Fixing nut beneath head: 22.4 N.m   |
| Shape Of Signaling Unit Head              | Round   |
| Cap/Operator Or Lens Colour               | Yellow  |
| Connections - Terminals                   | Faston connectors, connection size: $6.35 \times 0.8$ mm conforming to IEC 60947-1<br>Forked type tag connectors, connection size: $6.5$ mm conforming to IEC 60947-1<br>Screw clamp terminals, <= $2 \times 1.5$ mm <sup>2</sup> with cable end conforming to IEC 60947-1<br>Screw clamp terminals, $1 \times 0.222 \times 2.5$ mm <sup>2</sup> without cable end conforming to IEC 60947-1<br>60947-1 |
| Tightening Torque                         | 0.81.2 N.m conforming to IEC 60947-1  |
| Shape Of Screw Head                       | Cross compatible with JIS No 1 screwdriver<br>Cross compatible with Philips no 1 screwdriver<br>Cross compatible with pozidriv No 1 screwdriver<br>Slotted compatible with flat Ø 4 mm screwdriver<br>Slotted compatible with flat Ø 5.5 mm screwdriver   |
| [Ui] Rated Insulation Voltage             | 250 V (pollution degree 3) conforming to IEC 60947-1  |
| [Uimp] Rated Impulse Withstand<br>Voltage | 6 kV conforming to IEC 60947-1  |

| Signalling Type           | Steady   |
|---------------------------|----------|
| Bulb Base                 | BA 9s    |
| Light Block Supply        | Direct   |
| [Us] Rated Supply Voltage | <= 250 V |
| Compatibility Code        | ХВ7      |

## Environment

| Protective Treatment                     | тн  |
|--|---|
| Ambient Air Temperature For<br>Storage   | -4070 °C  |
| Ambient Air Temperature For<br>Operation | -2555 °C  |
| Ip Degree Of Protection                  | IP20 (rear face) conforming to IEC 60529<br>IP54 (front face) conforming to IEC 60529     |
| Nema Degree Of Protection                | NEMA 12   |
| Standards                                | CSA C22.2 No 14<br>UL 508<br>IEC 60947-5-1<br>IEC 60947-1<br>JIS C8201-5-1<br>JIS C8201-1 |
| Vibration Resistance                     | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6   |
| Shock Resistance                         | 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27     |
| Electromagnetic Compatibility            | Disturbing field emission class B conforming to IEC 55011                                 |

# **Packing Units**

| J                            |           |
|------------------------------|-----------|
| Unit Type Of Package 1       | PCE       |
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 3.000 cm  |
| Package 1 Width              | 3.000 cm  |
| Package 1 Length             | 5.500 cm  |
| Package 1 Weight             | 17.000 g  |
| Unit Type Of Package 2       | BB1       |
| Number Of Units In Package 2 | 10        |
| Package 2 Height             | 5.000 cm  |
| Package 2 Width              | 11.000 cm |
| Package 2 Length             | 16.000 cm |
| Package 2 Weight             | 174.000 g |
| Unit Type Of Package 3       | S01       |
| Number Of Units In Package 3 | 100       |
| Package 3 Height             | 15.000 cm |
| Package 3 Width              | 15.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 2.059 kg  |

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes


#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration  |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |

**Dimensions Drawings** 

#### Pilot Light with Screw Terminal

#### Dimensions




e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).

Mounting and Clearance


#### Mounting

#### **Diameter of Finished Fixing Holes**



- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value: Ø 22.3 (0; + 0.4) mm/Ø 0.88 (0; + 0.02) in.

#### Faston Clip Connection




#### "U" Type Tag Connection



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

Connections and Schema

#### Wiring Diagram



(1) bulb BA 9s