Product data sheet





Contactor, Tesys Deca, 3P(3NO),AC-3/AC-3e/<=440V 50A,240V AC 50/60Hz coil, screw clamp terminals

LC1D50U7

(!) Discontinued on: 21/09/2010

! Discontinued

Main		
Range	TeSys	
Range Of Product	TeSys Deca	
Product Or Component Type	Contactor	
Device Short Name	LC1D	
Contactor Application	Resistive load Motor control	
Utilisation Category	AC-3 AC-4 AC-2 AC-1 AC-3e	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz	
[le] Rated Operational Current	50 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 50 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
[Uc] Control Circuit Voltage	240 V AC 50/60 Hz	

Complementary

Motor Power Kw	22 kW at 380400 V AC 50 Hz (AC-3)
	25 kW at 415 V AC 50 Hz (AC-3)
	30 kW at 440 V AC 50 Hz (AC-3)
	30 kW at 500 V AC 50 Hz (AC-3)
	33 kW at 660690 V AC 50 Hz (AC-3)
	15 kW at 220230 V AC 50 Hz (AC-3)
	11 kW at 400 V AC 50 Hz (AC-4)
	30 kW at 1000 V AC 50 Hz (AC-3)
	22 kW at 380400 V AC 50 Hz (AC-3e)
	25 kW at 415 V AC 50 Hz (AC-3e)
	30 kW at 440 V AC 50 Hz (AC-3e)
	30 kW at 500 V AC 50 Hz (AC-3e)
	33 kW at 660690 V AC 50 Hz (AC-3e)
	15 kW at 220230 V AC 50 Hz (AC-3e)
	30 kW at 1000 V AC 50 Hz (AC-3e)
Motor Power Hp	3 hp at 115 V AC 60 Hz for 1 phase motors
	7.5 hp at 230/240 V AC 60 Hz for 1 phase motors
	15 hp at 200/208 V AC 60 Hz for 3 phases motors
	15 hp at 230/240 V AC 60 Hz for 3 phases motors
	40 hp at 460/480 V AC 60 Hz for 3 phases motors
	40 hp at 575/600 V AC 60 Hz for 3 phases motors
Compatibility Code	LC1D
Pole Contact Composition	3 NO
Protective Cover	With

[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C) for control circuit 80 A (at 60 °C) for power circuit
Irms Rated Making Capacity	900 A at 440 V for power circuit conforming to IEC 60947 140 A AC for control circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	900 A at 440 V for power circuit conforming to IEC 60947
Associated Fuse Rating	10 A gG for control circuit conforming to IEC 60947-5-1 100 A gG at <= 690 V coordination type 1 for power circuit 100 A gG at <= 690 V coordination type 2 for power circuit
Power Dissipation Per Pole	3.7 W AC-3 9.6 W AC-1 3.7 W AC-3e
[Ui] Rated Insulation Voltage	Control circuit: 600 V CSA certified Control circuit: 600 V UL certified Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Control circuit: 690 V conforming to IEC 60947-1 Power circuit: 690 V conforming to IEC 60947-1
Overvoltage Category	III
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	6000000 cycles
Control Circuit Type	AC at 50/60 Hz
Coil Technology	Without built-in bidirectional peak limiting diode suppressor
Control Circuit Voltage Limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz
Inrush Power In Va	140 VA cos phi 0.75 (at 20 °C) 160 VA cos phi 0.75 (at 20 °C)
Hold-In Power Consumption In Va	13 VA 60 Hz cos phi 0.3 (at 20 °C) 15 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	45 W at 50/60 Hz for control circuit
Operating Time	419 ms opening 1226 ms closing
Maximum Operating Rate	3600 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: rigid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: rigid Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Power circuit: screw terminals 1 2.525 mm² - cable stiffness: rigid Power circuit: screw terminals 2 2.516 mm² - cable stiffness: flexible without cable end Power circuit: screw terminals 1 2.525 mm² - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.516 mm² - cable stiffness: flexible without cable end Power circuit: screw terminals 2 2.525 mm² - cable stiffness: flexible with cable end Power circuit: screw terminals 2 2.510 mm² - cable stiffness: flexible with cable end Power circuit: screw terminals 2 2.510 mm² - cable stiffness: flexible with cable end
Tightening Torque	Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver Philips No 2 Power circuit: 5 N.m - on screw terminal - with screwdriver flat Ø 6 to Ø 8 mm Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver pozidriv No 2
Auxiliary Contact Composition	1 NO +1 NC

Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Minimum Switching Voltage	17 V for control circuit
Minimum Switching Current	5 mA for control circuit
Insulation Resistance	> 10 MOhm for control circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Mounting Support	Rail Plate
Environment	
Standards	IEC 60947-5-1 EN 60947-4-1 UL 508 CSA C22.2 No 14 EN 60947-5-1 IEC 60947-4-1
Product Certifications	BV CCC LROS (Lloyds register of shipping) DNV GOST GL RINA UL CSA UKCA
lp Degree Of Protection	IP2X conforming to IEC 60529 IP2X conforming to VDE 0106
Climatic Withstand	conforming to IACS E10 exposure to damp heat
Operating Altitude	03000 m
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Shocks contactor opened (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms) Vibrations contactor opened (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz)
Height	127 mm
Width	75 mm
Depth	119 mm
Net Weight	1.4 kg
Packing Units	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.500 cm
Package 1 Width	13.200 cm

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.500 cm
Package 1 Width	13.200 cm
Package 1 Length	8.200 cm
Package 1 Weight	1.431 kg
Unit Type Of Package 2	S02
Number Of Units In Package 2	5

Package 2 Height	15.000 cm	
Package 2 Width	30.000 cm	
Package 2 Length	40.000 cm	
Package 2 Weight	7.561 ka	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
⊘	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations