Product data sheet

Specifications





switch disconnector, Compact INS800, 800 A, standard version with black rotary handle, 3 poles

31330

① Discontinued

Main

| Main | | |
|--|--|--|
| Range | ComPact | |
| Product Name | ComPacT INS | |
| Product Or Component Type | Switch disconnector | |
| Poles Description | 3P | |
| Network Type | AC DC | |
| Network Frequency | 50/60 Hz | |
| [le] Rated Operational Current | AC-21A: 800 A AC 50/60 Hz 220/240 V AC-21A: 800 A AC 50/60 Hz 440/480 V AC-21A: 800 A AC 50/60 Hz 480 V NEMA AC-21A: 800 A AC 50/60 Hz 500/525 V AC-21A: 800 A AC 50/60 Hz 660/690 V AC-21A: 800 A AC 50/60 Hz 220/240 V AC-22A: 800 A AC 50/60 Hz 230/415 V AC-22A: 800 A AC 50/60 Hz 480 V NEMA AC-22A: 800 A AC 50/60 Hz 240/480 V AC-22A: 800 A AC 50/60 Hz 480 V NEMA AC-22A: 800 A AC 50/60 Hz 480 V NEMA AC-22A: 800 A AC 50/60 Hz 480 V NEMA AC-22A: 800 A AC 50/60 Hz 500/525 V AC-22A: 800 A AC 50/60 Hz 500/525 V AC-23A: 800 A AC 50/60 Hz 660/690 V AC-23A: 800 A AC 50/60 Hz 220/240 V AC-23A: 800 A AC 50/60 Hz 380/415 V AC-23A: 800 A AC 50/60 Hz 20/240 V AC-23A: 800 A AC 50/60 Hz 20/252 V AC-23A: 800 A AC 50/60 Hz 380/415 V AC-23A: 800 A AC 50/60 Hz 440/480 V AC-23A: 800 A AC 50/60 Hz 500/525 V AC-23A: 800 A AC 50/60 Hz 660/690 V DC-21A: 800 A DC 125 V 2 poles in series DC-22A: 800 A DC 125 V 2 poles in series | |
| [Ui] Rated Insulation Voltage | 1000 V AC 50/60 Hz | |
| [Uimp] Rated Impulse Withstand Voltage | 12 kV | |
| [Ith] Conventional Free Air Thermal Current | 800 A at 60 °C | |
| [Icm] Rated Short-Circuit Making Capacity | 330 kA with upstream protection circuit breaker 690 V AC at 50/60 Hz 75 kA switch-disconnector alone 690 V AC at 50/60 Hz | |
| [Ue] Rated Operational Voltage | 125 V DC 690 V AC 50/60 Hz | |
| Suitability For Isolation | Yes | |
| Contact Position Indicator | Yes | |
| Visible Break | No | |
| Pollution Degree | 3 | |

Complementary

List Price displayed is VAT EXCLUSIVE.

| Control Type | Direct front rotary handle |
|---|--|
| Handle Colour | Black |
| Mounting Mode | Fixed |
| Mounting Support | Rail Plate |
| Upside Connection | Front |
| Downside Connection | Front |
| Maximum Power | AC-23: 250 kW at 220/240 V AC 50/60 Hz AC-23: 400 kW at 380/400 V AC 50/60 Hz AC-23: 500 kW at 415 V AC 50/60 Hz AC-23: 560 kW at 500/525 V AC 50/60 Hz AC-23: 710 kW at 660/690 V AC 50/60 Hz |
| Rated Duty | Uninterrupted |
| Intermittent Duty Class | Class 120 - 60 % |
| [Icw] Rated Short-Time Withstand Current | 10 kA during 20 s conforming to IEC 60947-3 20 kA during 3 s conforming to IEC 60947-3 35 kA during 1 s conforming to IEC 60947-3 42 kA during 0.8 s conforming to IEC 60947-3 50 kA during 0.5 s conforming to IEC 60947-3 8 kA during 30 s conforming to IEC 60947-3 |
| Mechanical Durability | 3000 cycles |
| Electrical Durability | AC-21A: 500 cycles 220/240 V AC 50/60 Hz AC-21A: 500 cycles 380/415 V AC 50/60 Hz AC-21A: 500 cycles 440/480 V AC 50/60 Hz AC-21A: 500 cycles 480 V AC 50/60 Hz conforming to NEMA AC-21A: 500 cycles 500/525 V AC 50/60 Hz AC-21A: 500 cycles 660/690 V AC 50/60 Hz AC-21A: 500 cycles 660/690 V AC 50/60 Hz AC-22A: 500 cycles 220/240 V AC 50/60 Hz AC-22A: 500 cycles 380/415 V AC 50/60 Hz AC-22A: 500 cycles 440/480 V AC 50/60 Hz AC-22A: 500 cycles 480 V AC 50/60 Hz AC-22A: 500 cycles 500/525 V AC 50/60 Hz AC-22A: 500 cycles 660/690 V AC 50/60 Hz AC-22A: 500 cycles 660/690 V AC 50/60 Hz AC-23A: 500 cycles 380/415 V AC 50/60 Hz AC-23A: 500 cycles 380/415 V AC 50/60 Hz AC-23A: 500 cycles 440/480 V AC 50/60 Hz AC-23A: 500 cycles 480 V AC 50/60 Hz AC-23A: 500 cycles 480 V AC 50/60 Hz AC-23A: 500 cycles 480 V AC 50/60 Hz AC-23A: 500 cycles 500/525 V AC 50/60 Hz AC-23A: 500 cycles 125 V DC 2 poles in series DC-22A: 500 cycles 125 V DC 2 poles in series DC-23A: 500 cycles 125 V DC 2 poles in series |
| Connection Pitch | 70 mm |
| Height | 300 mm |
| Width | 340 mm |
| Depth | 146.5 mm |
| Net Weight Environment | 14 kg |
| Standards | IEC 60947-3 IEC 60947-1 |
| Product Certifications | KEMA-KEUR |
| Ip Degree Of Protection | IP40 conforming to IEC 60529 |

May 14, 2024

-25...70 °C

-50...85 °C

IK07 conforming to EN 50102

Ik Degree Of Protection

Ambient Air Temperature For Operation

Ambient Air Temperature For Storage

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 20.000 cm |
| Package 1 Width | 33.000 cm |
| Package 1 Length | 35.500 cm |
| Package 1 Weight | 15.100 kg |

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |