Product data sheet

Specifications



voltage release MX - 24 V DC/AC 50/60Hz

47370



Main

Range	MasterPacT
Range Of Product	MasterPact NT MasterPact NW
	MasterPact NW DC
Device Short Name	second MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Second opening coil Instantaneous voltage release
Control Type	Standard
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz 2430 V DC
Circuit Breaker Mounting Mode	Fixed
Range Compatibility	Masterpact MasterPact NT
	Masterpact MasterPact NW Masterpact MasterPact NW DC

Complementary

Operating Threshold	0.71.1 x Un opening
Response Time	50 ms +/- 10 % for MasterPact NT 50 ms +/- 10 % for MasterPact NW
Supply Holding Power	4.5 VA

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	6.1 cm
Package 1 Length	8.3 cm
Package 1 Weight	1.16 kg

Contractual warranty

Warranty

18 months

List Price displayed is VAT EXCLUSIVE.

Life Is On Schneider

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information