Product datasheet

Specification





Reflex iC60H Ti24 25 A 4P curve D integrated control MCB

A9C66425

! Discontinued on: 25 Nov 2020

(!) Discontinued

Main

| Device Application | Distribution Control | |
|---------------------------|------------------------------------|--|
| Range | Acti9 | |
| Product Name | Reflex iC60 | |
| Device Short Name | Reflex iC60H | |
| Product Or Component Type | Integrated control circuit breaker | |
| Poles Description | 4P | |
| Number Of Protected Poles | 4 | |
| Network Type | AC | |
| Trip Unit Technology | ology Thermal-magnetic | |
| Curve Code | D | |

Complementary

| [In] Rated Current | 25 A |
|-------------------------------|--|
| Network Frequency | 50/60 Hz |
| Breaking Capacity Code | н |
| Breaking Capacity | 30 kA Icu at 220240 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 kA Icu at 380415 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| [Ui] Rated Insulation Voltage | 500 V AC |
| Contact Position Indicator | Yes |
| Control Type | Toggle Remote control by pulse ON/OFF button Remote control by continuous command |
| Control Signal Type | Maintained very low voltage Impulse Maintained |
| Local Signalling | Flashing LED: device overheat Green LED: device ON Flashing LED: device tripped Red LED: fault Flashing LED: device ready |
| [Uc] Control Circuit Voltage | 230 V AC 50/60 Hz 24 V AC 50/60 Hz 48 V AC 50/60 Hz 24 V DC 48 V DC |
| [Us] Rated Supply Voltage | 230 V AC at 50/60 Hz |

| Mounting Mode | Fixed | |
|-----------------------------|-----------------------------------|--|
| Mounting Support | 35 mm symmetrical DIN rail | |
| 9 Mm Pitches | 13 | |
| Height | 84 mm | |
| Width | 117 mm | |
| Depth | 77 mm | |
| Colour | White | |
| Mechanical Durability | 50000 cycles | |
| Electrical Durability | AC-1: 50000 cycles AC 50 Hz | |
| Provision For Padlocking | dlocking Padlockable | |
| Locking Options Description | scription Padlock in OFF position | |
| Earth-Leakage Protection | kage Protection Separate block | |
| Product Compatibility | With PLC | |

Environment

| Ip Degree Of Protection | IP20 conforming to IEC 60529 | |
|-------------------------|------------------------------|--|
| Pollution Degree | 3 | |
| Tropicalisation | 2 | |
| Relative Humidity | 93 % at 40 °C | |

Packing Units

| Unit Type Of Package 1 | PCE |
|----------------------------------|------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 9.000 cm |
| Package 1 Width | 11.400 cm |
| Package 1 Length | 16.700 cm |
| Package 1 Weight | 814.900 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 14 |
| Package 2 Height | 30.000 cm |
| | |
| Package 2 Width | 30.000 cm |
| Package 2 Width Package 2 Length | 30.000 cm 40.000 cm |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Mercury Free | |
|----------|------------------------------------|-----|
| ⊘ | Rohs Exemption Information | Yes |
| ② | Halogen Free Plastic Parts Product | |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |