Product datasheet

Specifications





rectified and filtered power supply - 1 or 2-phase - 400 V AC - 24 V - 10 A

ABL8FEQ24100

Main

Range Of Product	Modicon Rectified			
Product Or Component Type	Power supply			
Power Supply Type	Rectified and filtered			
Rated Power In W	240 W			
Nominal Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2			
Output Voltage	24 V DC			
Power Supply Output Current	10 A			
Anti-Harmonic Filter	Low frequency harmonic currents			
Product Certifications	cULus EAC UL 508 KC			

Complementary

Network Frequency Limits	4763 Hz
Input Voltage Limits	360440 V 207253 V
Power Factor	0.783 at 230 V 0.834 at 400 V
Efficiency	80 %
Power Dissipation In W	48 W
Output Coupling	Series Parallel
Output Protection Type	Against overvoltage, protection technology: 2 J peak limiter Against overload and short-circuits, protection technology: external fuse, 12 A
Hold-Up Time	15 ms
Status Led	1 LED (green) output voltage 1 LED (orange) input voltage
Residual Ripple	<= 1200 MV
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 2.55 x 4 mm² AWG 14AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 2.51 x 4 mm² AWG 14AWG 11 For output connection: screw type terminals, connection capacity: 4 x 4 mm² AWG 11
Depth	185 mm
Height	152.0 mm
Width	123 mm

Net Weight	7.60 kg
Compatibility Code	ABL8F

Environment

Ip Degree Of Protection	IP20 conforming to EN/IEC 60529			
Ambient Air Temperature For Operation	-2060 °C			
Ambient Air Temperature For Storage	-4080 °C			
Relative Humidity	095 % without condensation or dripping water			
Operating Altitude	3000 m			
Safety Class	Class I conforming to VDE 0106-1			
Dielectric Strength	2000 V between input and ground 4600 V between input and output 500 V between output and ground			
Other Environmental Characteristic	EMC conforming to IEC 62041 Safety conforming to EN/IEC 61558-2-6 Safety conforming to UL 508 Safety conforming to UL 60950-1 EMC conforming to EN/IEC 61000-3-2			

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	27.000 cm
Package 1 Width	26.500 cm
Package 1 Length	15.000 cm
Package 1 Weight	8.112 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	24
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	204.500 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance




Certifications & Standards

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		

ABL8FEQ24100

Dimensions Drawings

Dimensions



Dimensions in mm


Dimensione in min					
а	b	С	G	J	Ø
123	185	153	82	136	6.5

Dimensions in in.

а	b	С	G	J	Ø
4.84	7.28	6.02	3.23	5.35	0.25

Connections and Schema

Internal Wiring Diagram




Product datasheet

ABL8FEQ24100

Performance Curves

Load Limits Curve



- (1) Nominal line supply + 10%
- (2) Nominal line supply
- (3) Nominal line supply 10%