## **Product datasheet**

Specifications





# TeSys K control relay , 2 NO + 2 NC , <= 690 V , 115 V AC coil

CA2KN223FE7

() Discontinued on: 1 Nov 2020

#### (!) Discontinued

#### Main

| Range                          | TeSys                                     |  |
|--------------------------------|---|--|
| Product Name                   | TeSys CAK                                 |  |
| Product Or Component Type      | Control relay                             |  |
| Device Short Name              | CA2K                                      |  |
| Contactor Application          | Control circuit                           |  |
| Utilisation Category           | AC-15<br>DC-13                            |  |
| Pole Contact Composition       | 2 NO + 2 NC                               |  |
| [Ue] Rated Operational Voltage | ed Operational Voltage <= 690 V <= 400 Hz |  |
| Control Circuit Type           | AC at 50/60 Hz                            |  |
| [Uc] Control Circuit Voltage   | 115 V AC 50/60 Hz                         |  |
|                                |   |  |

#### Complementary

| [Ith] Conventional Free Air<br>Thermal Current | 10 A (at 50 °C)   |
|--|---|
| Irms Rated Making Capacity                     | 110 A conforming to IEC 60947   |
| Associated Fuse Rating                         | 10 A gG conforming to IEC 60947<br>10 A gG conforming to VDE 0660   |
| [Ui] Rated Insulation Voltage                  | 690 V conforming to IEC 60947<br>750 V conforming to VDE 0110 group C<br>690 V conforming to BS 5424<br>600 V conforming to CSA C22.2 No 14                                       |
| Mounting Support                               | Plate<br>Rail   |
| Connections - Terminals                        | Spring terminals 1 cable(s) 0.751.5 mm <sup>2</sup> solid<br>Spring terminals 1 cable(s) 0.751.5 mm <sup>2</sup> flexible without cable end                                       |
| Control Circuit Voltage Limits                 | Drop-out: 0.20.75 Uc (at <50 °C)<br>Operational: 0.81.15 Uc (at <50 °C)   |
| Operating Time                                 | 1020 ms coil de-energisation and NO opening<br>1020 ms coil energisation and NO closing<br>1525 ms coil de-energisation and NC closing<br>515 ms coil energisation and NC opening |
| Mechanical Durability                          | 10 Mcycles  |
| Maximum Operating Rate                         | 10000 cyc/h   |
| Immunity To Microbreaks                        | 2 ms  |
| Inrush Power In Va                             | 30 VA (at 20 °C)  |

| Hold-In Power Consumption In Va | 4.5 VA (at 20 °C) |
|---------------------------------|-------------------|
| Heat Dissipation                | 1.3 W             |
| Minimum Switching Voltage       | 17 V              |
| Minimum Switching Current       | 5 mA              |
| Non Overlap Distance            | 0.5 mm            |
| Insulation Resistance           | > 10 MOhm         |
| Height                          | 58 mm             |
| Width                           | 45 mm             |
| Depth                           | 57 mm             |
| Net Weight                      | 0.18 kg           |

## Environment

| Standards                                | EN/IEC 60947-4-1<br>GB/T 14048.4<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1<br>JIS C8201-4-1  |  |
|--|--|--|
| Product Certifications                   | CB Scheme<br>CCC<br>UL<br>CSA<br>EAC<br>CE<br>UKCA   |  |
| Protective Treatment                     | TC conforming to IEC 60068   |  |
| Ambient Air Temperature For<br>Operation | -2550 °C   |  |
| Ambient Air Temperature For<br>Storage   | -5080 °C   |  |
| Operating Altitude                       | 2000 m without derating  |  |
| Flame Retardance                         | Retardance V1 conforming to UL 94<br>Requirement 2 conforming to NF F 16-101<br>Requirement 2 conforming to NF F 16-102  |  |
| Mechanical Robustness                    | Vibrations contactor open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6<br>Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6<br>Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27<br>Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 |  |

## **Packing Units**

| -                            |        |
|------------------------------|--------|
| Unit Type Of Package 1       | PCE    |
| Number Of Units In Package 1 | 1      |
| Package 1 Height             | 4.8 cm |
| Package 1 Width              | 6.5 cm |
| Package 1 Length             | 6.2 cm |
| Package 1 Weight             | 207 g  |

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc

| Toxic Heavy Metal Free     |     |
|----------------------------|-----|
| Mercury Free               |     |
| Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Eu Rohs Directive        | Compliant   |
|--------------------------|---|
|                          | EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                 |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |