Product datasheet

Specification





circuit breaker EasyPact EZC250H - TMD - 250 A - 4 poles 4d

EZC250H44250

! Discontinued on: 1 Nov 2020

① Discontinued

Main

Walli		
Range Of Product	EasyPact	
Product Or Component Type	Circuit breaker	
Device Short Name	Easypact EZC250H	
Circuit Breaker Name	Easypact EZC250H	
Device Application	Distribution	
Poles Description	4P	
Protected Poles Description	4t	
Network Type	AC DC	
Network Frequency	50/60 Hz	
[In] Rated Current	250 A at 40 °C	
[Ui] Rated Insulation Voltage	690 V AC 50/60 Hz conforming to IEC 60947-2	
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947-2	
[Ue] Rated Operational Voltage	550 V AC 50/60 Hz conforming to IEC 60947-2 250 V DC conforming to IEC 60947-2	
Breaking Capacity Code	Н	
Breaking Capacity	10 kA Icu at 550 V AC 50/60 Hz conforming to IEC 60947-2 25 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 30 kA Icu at 125 V DC 1P conforming to IEC 60947-2 30 kA Icu at 250 V DC 2P conforming to IEC 60947-2 85 kA Icu at 220240 V AC 50/60 Hz conforming to IEC 60947-2 36 kA Icu at 380415 V AC 50/60 Hz conforming to IEC 60947-2	
[Ics] Rated Service Breaking Capacity	5 kA at 550 V AC 50/60 Hz conforming to IEC 60947-2 15 kA at 125 V DC conforming to IEC 60947-2 15 kA at 250 V DC conforming to IEC 60947-2 12.5 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 18 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2 42.5 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2	
Suitability For Isolation	Yes conforming to IEC 60947-2	
Utilisation Category	Category A	
Trip Unit Name	TM-D	
Trip Unit Technology Thermal-magnetic		
Trip Unit Rating	250 A at 50 °C	
Protection Type	Overload protection Short-circuit protection	
Pollution Degree	3 conforming to IEC 60947	

Complementary

Control Type	Toggle	
Mounting Mode	Fixed	
Mounting Support	Backplate	
Upside Connection	Front	
Downside Connection	Front	
Mechanical Durability	10000 cycles	
Electrical Durability	Category A: 5000 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2	
Connection Pitch	35 mm	
Local Signalling	Positive contact indication	
Neutral Protection Setting	Without protection	
Earth-Leakage Protection	Without	
Height	165 mm	
Width	140 mm	
Depth	60 mm	

Environment

Standards	JIS C8201-2-2 GB/T 14048.2 EN/IEC 60947-1 EN/IEC 60947-2	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to EN 50102	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-3585 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	11.3 cm
Package 1 Length	18 cm
Package 1 Weight	2.24 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins