Product datasheet

Specification





Linergy passthrough terminal block

- 4mm² 32A single-level 1x1 screw
- blue

NSYTRV42BL

Main

Range	Linergy	
Product Name	Linergy TR	
Product Or Component Type	Terminal block	
Device Short Name	TRV	
Accessory / Separate Part Category	Connection accessory	
Terminal Block Type	Passthrough	
Terminal Block Level	1	
Mounting Mode	Clip-on	
Nominal Cross Section	Section 4 mm ²	
Length	47.7 mm	
Colour	Blue	
Quantity Per Set Set of 50		

Complementary

Width	6.2 mm	
Height	47.5 mm	
Connections - Terminals	1 x screw terminal: upstream (M3) 1 x screw terminal: downstream (M3)	
Number Of Connections	2	
Connection Position	Sideways	
Number Of Measurement Input	2	
Cable Cross Section	0.146 mm², solid cable with cable end 0.24 mm², flexible cable with cable end 0.26 mm², solid cable without cable end 0.26 mm², flexible cable without cable end	
Tightening Torque	0.60.8 N.m	
Wire Stripping Length	9 mm	
Tool Type	Connection: screwdriver Disconnection: screwdriver	
[Ue] Rated Operational Voltage	1000 V conforming to EN/IEC 60947-7-1 600 V CSA 690 V conforming to ATEX Exe II Ex II 2 GD	

600 V cURus

[In] Rated Current	32 A conforming to EN/IEC 60947-7-1 30 A CSA 30 A conforming to ATEX Exe II Ex II 2 GD
	30 A cURus
Material	Polyamide 6/6: insulating case
	Copper alloy: connector and screw
	Copper alloy: commoning link
	Chromium-nickel steel: spring
Dielectric Loss	0.01 at 1 MHz conforming to IEC 60250
	0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric Constant	3.7 at 1 MHz
Resistivity	10000 M Ω .m conforming to IEC 60093
	10000 MΩ.m conforming to VDE 0303-T30
Surface Resistance	1000 G Ω conforming to IEC 60093
	1000 G Ω conforming to VDE 0303-T30
Creep Resistance	500 CTI (> 400 kB) conforming to IEC 60093
•	500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame Retardance	V0, thickness0.8 mm conforming to UL 94
Net Weight	9.4 g
Range Compatibility	Prisma G Prisma P
	Prisma P
	Prisma Pack
	Spacial
	Kaedra
	Pragma
	TeSys
Product Compatibility	Spacial enclosures
Environment	
Environment Product Certifications	DNV
	DNV VDE
	VDE
	VDE cURus ATEX GL
	VDE cURus ATEX GL CSA
	VDE cURus ATEX GL CSA IEC-Ex
	VDE cURus ATEX GL CSA
	VDE cURus ATEX GL CSA IEC-Ex EAC
Product Certifications Dielectric Strength	VDE cURus ATEX GL CSA IEC-EX EAC LR 1000 V conforming to IEC 60243-1
Product Certifications	VDE cURus ATEX GL CSA IEC-EX EAC LR
Product Certifications Dielectric Strength Ambient Air Temperature For Operation	VDE cURus ATEX GL CSA IEC-Ex EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to IEC 60216-1
Product Certifications Dielectric Strength Ambient Air Temperature For	VDE cURus ATEX GL CSA IEC-Ex EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to IEC 60216-1
Product Certifications Dielectric Strength Ambient Air Temperature For Operation	VDE cURus ATEX GL CSA IEC-Ex EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to IEC 60216-1
Dielectric Strength Ambient Air Temperature For Operation Packing Units	VDE cURus ATEX GL CSA IEC-Ex EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to VDE 0304-T21
Dielectric Strength Ambient Air Temperature For Operation Packing Units Unit Type Of Package 1	VDE cURus ATEX GL CSA IEC-EX EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to VDE 0304-T21 PCE
Dielectric Strength Ambient Air Temperature For Operation Packing Units Unit Type Of Package 1 Number Of Units In Package 1	VDE cURus ATEX GL CSA IEC-EX EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to VDE 0304-T21 PCE
Product Certifications Dielectric Strength Ambient Air Temperature For Operation Packing Units Unit Type Of Package 1 Number Of Units In Package 1 Package 1 Height	VDE cURus ATEX GL CSA IEC-Ex EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to VDE 0304-T21 PCE 1 0.800 cm
Dielectric Strength Ambient Air Temperature For Operation Packing Units Unit Type Of Package 1 Number Of Units In Package 1 Package 1 Height Package 1 Width	VDE cURus ATEX GL CSA IEC-EX EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to VDE 0304-T21 PCE 1 0.800 cm 4.800 cm
Product Certifications Dielectric Strength Ambient Air Temperature For Operation Packing Units Unit Type Of Package 1 Number Of Units In Package 1 Package 1 Height Package 1 Width Package 1 Length	VDE cURus ATEX GL CSA IEC-EX EAC LR 1000 V conforming to IEC 60243-1 -40130 °C conforming to VDE 0304-T21 PCE 1 0.800 cm 4.800 cm

Number Of Units In Package 2

Package 2 Height

Package 2 Width

50

5.500 cm

6.200 cm

Package 2 Length	32.000 cm
Package 2 Weight	476.000 g
Unit Type Of Package 3	S03
Number Of Units In Package 3	1150
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	11.430 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations