# **Product datasheet**





## iPRD65r modular surge arrester -1P + N - 350V - with remote transfert

A9L65501

#### Main

| Range Of Product            | Acti9                                   |
|-----------------------------|---|
| Product Name                | Acti9 iPRD                              |
| Product Or Component Type   | Surge arrester with pluggable cartridge |
| Device Short Name           | iPRD65r                                 |
| Device Application          | Distribution                            |
| Standards                   | EN 61643-11:2012<br>IEC 61643-11:2011   |
| Product Certifications      | CE                                      |
| Quality Labels              | NF<br>KEMA-KEUR                         |
| Poles Description           | 1P + N                                  |
| Remote Signalling           | With                                    |
| Signal Contacts Composition | 1 SD (1 C/O)                            |
| Surge Arrester Type         | Electrical distribution network         |
| Earthing System             | TN-S<br>TT                              |

### Complementary

| Surge Arrester Class Type                    | Type 2  |
|--|---|
| Surge Arrester Technology                    | MOV + GDT   |
| [Ue] Rated Operational Voltage               | 230/400 V AC (+/- 10 %) at 50/60 Hz   |
| [In] Nominal Discharge Current               | Common mode: 20 kA (L/PE) Common mode: 20 kA (N/PE) Differential mode: 20 kA (L/N)  |
| [Imax] Maximum Discharge<br>Current          | Common mode: 65 kA L/PE<br>Common mode: 65 kA N/PE<br>Differential mode: 65 kA L/N  |
| [Uc] Maximum Continuous<br>Operating Voltage | Common mode: 260 V N/PE<br>Common mode: 350 V L/PE<br>Differential mode: 350 V L/N  |
| Maximum [Up] Voltage Protection<br>Level     | Common mode <1.5 kV type 2 N/PE<br>Differential mode <1.5 kV type 2 L/N   |
| [Ut] Temporary Overvoltage                   | 337 V L/N 5 s withstand<br>1200 V N/PE 200 ms safe failure mode<br>442 V L/PE 5 s withstand<br>1453 V L/PE 200 ms safe failure mode |

| Disconnector Device Type      | Associated circuit breaker IC60N 50 A curve C - Icu 10 kA Associated circuit breaker iC60H 50 A curve C - Icu 15 kA Associated circuit breaker NG125N 50 A curve C - Icu 25 kA Associated circuit breaker NG125H 50 A curve C - Icu 36 kA Associated circuit breaker NG125L 50 A curve C - Icu 50 kA Associated fuse gG 80 A - Icu 50 kA |
|-------------------------------|--|
| Signalling Circuit Voltage    | 0.25 A/250 V AC 50/60 Hz   |
| Mounting Mode                 | Clip-on (DIN rail)   |
| 9 Mm Pitches                  | 4  |
| Height                        | 85 mm  |
| Width                         | 36 mm  |
| Depth                         | 69 mm  |
| Net Weight                    | 0.238 kg   |
| Colour                        | White (RAL 9003)   |
| [Ipe] Ground Residual Current | 0.003 mA<br>0.6 mA   |
| Connections - Terminals       | Tunnel type terminal (downside) 2.535 mm <sup>2</sup> Tunnel type terminal (upside) 2.535 mm <sup>2</sup>  |
| Tightening Torque             | 2.5 N.m  |

### **Environment**

| Ik Degree Of Protection               | IK03 conforming to IEC 62262 |
|---------------------------------------|------------------------------|
| Relative Humidity                     | 595 %                        |
| Operating Altitude                    | 2000 m                       |
| Ambient Air Temperature For Operation | -2560 °C                     |
| Ambient Air Temperature For Storage   | -4085 °C                     |

# **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 4.2 cm   |
| Package 1 Width              | 7.2 cm   |
| Package 1 Length             | 9.2 cm   |
| Package 1 Weight             | 268 g    |
| Unit Type Of Package 2       | BB1      |
| Number Of Units In Package 2 | 6        |
| Package 2 Height             | 9 cm     |
| Package 2 Width              | 10 cm    |
| Package 2 Length             | 28 cm    |
| Package 2 Weight             | 1.679 kg |
| Unit Type Of Package 3       | S03      |
| Number Of Units In Package 3 | 54       |
| Package 3 Height             | 30 cm    |
| Package 3 Width              | 30 cm    |

| Package 3 Length | 40 cm     |  |
|------------------|-----------|--|
| Package 3 Weight | 15.685 kg |  |

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant EU RoHS Declaration  |
| China Rohs Regulation    | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile  |
| Circularity Profile      | End of Life Information  |