Product datasheet

Specification





Residual current circuit breaker (RCCB), Acti9 iID K, 4P, 25A, AC type, 300mA

A9R75425

Main

Range	Acti9	
Product Name	Acti9 iID K	
Product Or Component Type	Residual current circuit breaker (RCCB)	
Device Short Name	Name iID K	
Poles Description	4P	
Neutral Position	utral Position Left	
[In] Rated Current 25 A		
Network Type	AC	
Earth-Leakage Sensitivity	300 mA	
Earth-Leakage Protection Time Delay	Instantaneous	
Earth-Leakage Protection Class	Type AC	
Quality Labels	VDE	

Complementary

Device Location In System	Outgoer
Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	380415 V AC 50/60 Hz
Residual Current Tripping Technology	Voltage independent
Rated Breaking And Making Capacity	Idm 500 A Im 500 A
Rated Conditional Short-Circuit Current	GL63: Inc 4.5 kA K60: Inc 6 kA C60: Inc 6 kA
[Ui] Rated Insulation Voltage	440 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	4 kV
Surge Current	250 A
Contact Position Indicator	No
Control Type	Toggle
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 Mm Pitches	8
Height	85 mm

Width	72 mm	
Depth	69 mm	
Net Weight	0.37 kg	
Colour	White	
Mechanical Durability	5000 cycles	
Electrical Durability	AC-1: 2000 cycles	
Locking Options Description	otions Description Padlocking device	
Connections - Terminals	Tunnel type terminals top or bottom 135 mm² rigid Tunnel type terminals top or bottom 125 mm² flexible Tunnel type terminals top or bottom 125 mm² flexible with ferrule	
Wire Stripping Length	pping Length 16 mm for top or bottom connection	
Tightening Torque	ening Torque 3.5 N.m top or bottom	

Environment

Standards	EN/IEC 61008-1 EN/IEC 61008-2-1	
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529	
Pollution Degree	2	
Electromagnetic Compatibility	ty 8/20 μs impulse withstand, 200 A conforming to EN/IEC 61008-1	
Ambient Air Temperature For Operation	For -560 °C	
Ambient Air Temperature For Storage	Air Temperature For -4085 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.500 cm
Package 1 Width	7.500 cm
Package 1 Length	10.000 cm
Package 1 Weight	354.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	27
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	10.127 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
②	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations