Product datasheet

Specification





Residual current circuit breaker (RCCB), Acti9 iID K, 4P, 40A, AC type, 300mA

A9R75440

Main

| Range | Acti9 | |
|-------------------------------------|---|--|
| Product Name | Acti9 iID K | |
| Product Or Component Type | Residual current circuit breaker (RCCB) | |
| Device Short Name | iID K | |
| Poles Description | 4P | |
| Neutral Position | Left | |
| [In] Rated Current | 40 A | |
| Network Type | AC | |
| Earth-Leakage Sensitivity | 300 mA | |
| Earth-Leakage Protection Time Delay | Instantaneous | |
| Earth-Leakage Protection Class | Type AC | |
| Quality Labels | VDE | |

Complementary

| Device Location In System | Outgoer |
|---|--|
| Network Frequency | 50/60 Hz |
| [Ue] Rated Operational Voltage | 380415 V AC 50/60 Hz |
| Residual Current Tripping Technology | Voltage independent |
| Rated Breaking And Making Capacity | Idm 500 A Im 500 A |
| Rated Conditional Short-Circuit Current | GL63: Inc 4.5 kA K60: Inc 6 kA C60: Inc 6 kA |
| [Ui] Rated Insulation Voltage | 440 V AC 50/60 Hz |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV |
| Surge Current | 250 A |
| Contact Position Indicator | No |
| Control Type | Toggle |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| 9 Mm Pitches | 8 |
| Height | 85 mm |

| Width | 72 mm | |
|-----------------------------|--|--|
| Depth | 69 mm | |
| Net Weight | 0.37 kg | |
| Colour | White | |
| Mechanical Durability | 5000 cycles | |
| Electrical Durability | AC-1: 2000 cycles | |
| Locking Options Description | Padlocking device | |
| Connections - Terminals | Tunnel type terminals top or bottom 135 mm² rigid Tunnel type terminals top or bottom 125 mm² flexible Tunnel type terminals top or bottom 125 mm² flexible with ferrule | |
| Wire Stripping Length | 16 mm for top or bottom connection | |
| Tightening Torque | 3.5 N.m top or bottom | |

Environment

| Standards | EN/IEC 61008-1 EN/IEC 61008-2-1 | |
|---------------------------------------|---|--|
| Ip Degree Of Protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 | |
| Pollution Degree | 2 | |
| Electromagnetic Compatibility | 8/20 μs impulse withstand, 200 A conforming to EN/IEC 61008-1 | |
| Ambient Air Temperature For Operation | -560 °C | |
| Ambient Air Temperature For Storage | -4085 °C | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 7.500 cm |
| Package 1 Width | 8.500 cm |
| Package 1 Length | 10.000 cm |
| Package 1 Weight | 364.000 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 27 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 10.246 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |