# **Product datasheet**

Specifications





## Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 18A, 110V DC coil, spring terminals

LC1D183FD

(Discontinued on: Sep 19, 2023 AD

(!) Discontinued

#### Main

| mann                           |   |
|--------------------------------|---|
| Range                          | TeSys   |
| Range Of Product               | TeSys Deca  |
| Product Or Component Type      | Contactor   |
| Device Short Name              | LC1D  |
| Contactor Application          | Resistive load<br>Motor control   |
| Utilisation Category           | AC-1<br>AC-4<br>AC-3  |
| Poles Description              | 3P  |
| [Ue] Rated Operational Voltage | Power circuit: <= 690 V AC 25400 Hz<br>Power circuit: <= 300 V DC   |
| [le] Rated Operational Current | 18 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>32 A (at <60 °C) at <= 440 V AC AC-1 for power circuit<br>18 A (at <60 °C) AC AC-3e |
| [Uc] Control Circuit Voltage   | 110 V DC  |

#### Complementary

| 4 kW at 220230 V AC 50/60 Hz (AC-3)                         |  |
|---|--|
| 7.5 kW at 380400 V AC 50/60 Hz (AC-3)                       |  |
| 9 kW at 415440 V AC 50/60 Hz (AC-3)                         |  |
| 10 kW at 500 V AC 50/60 Hz (AC-3)                           |  |
| 10 kW at 660690 V AC 50/60 Hz (AC-3)                        |  |
| 4 kW at 400 V AC 50/60 Hz (AC-4)                            |  |
| 1 hp at 115 V AC 50/60 Hz for 1 phase motors                |  |
| 3 hp at 230/240 V AC 50/60 Hz for 1 phase motors            |  |
| 5 hp at 200/208 V AC 50/60 Hz for 3 phases motors           |  |
| 5 hp at 230/240 V AC 50/60 Hz for 3 phases motors           |  |
| 10 hp at 460/480 V AC 50/60 Hz for 3 phases motors          |  |
| 15 hp at 575/600 V AC 50/60 Hz for 3 phases motors          |  |
| LC1D  |  |
| 3 NO  |  |
| With  |  |
| 25 A (at 60 °C) for power circuit                           |  |
| 10 A (at 60 °C) for signalling circuit                      |  |
| 140 A AC for signalling circuit conforming to IEC 60947-5-1 |  |
| 250 A DC for signalling circuit conforming to IEC 60947-5-1 |  |
| 300 A at 440 V for power circuit conforming to IEC 60947    |  |
| 300 A at 440 V for power circuit conforming to IEC 60947    |  |
|   | 7.5 kW at 380400 V AC 50/60 Hz (AC-3)     9 kW at 415440 V AC 50/60 Hz (AC-3)     10 kW at 500 V AC 50/60 Hz (AC-3)     10 kW at 660690 V AC 50/60 Hz (AC-3)     4 kW at 400 V AC 50/60 Hz (AC-4)     1 hp at 115 V AC 50/60 Hz for 1 phase motors     3 hp at 230/240 V AC 50/60 Hz for 1 phase motors     5 hp at 200/208 V AC 50/60 Hz for 3 phases motors     5 hp at 230/240 V AC 50/60 Hz for 3 phases motors     10 hp at 460/480 V AC 50/60 Hz for 3 phases motors     15 hp at 575/600 V AC 50/60 Hz for 3 phases motors     15 hp at 575/600 V AC 50/60 Hz for 3 phases motors     15 hp at 575/600 V AC 50/60 Hz for 3 phases motors     15 hp at 575/600 V AC 50/60 Hz for 3 phases motors     16 hp at 460/480 V AC 50/60 Hz for 3 phases motors     17 hp at 575/600 V AC 50/60 Hz for 3 phases motors     18 hp at 575/600 V AC 50/60 Hz for 3 phases motors     19 hp at 60/480 V AC 50/60 Hz for 3 phases motors     10 hp at 460/480 V AC 50/60 Hz for 3 phases motors     10 hp at 60/480 V AC 50/60 Hz for 3 phases motors     15 hp at 575/600 V AC 50/60 Hz for 3 phases motors     10 hp at 60 °C) for power circuit     10 A (at 60 °C) for power circuit     10 A AC for signalling circuit conforming to IEC 60947-5-1     250 A DC for signalling circuit conforming to IEC 60947-5-1 <t< td=""></t<> |

Life Is On Schneider

| [Icw] Rated Short-Time Withstand<br>Current | 145 A 40 °C - 10 s for power circuit<br>240 A 40 °C - 1 s for power circuit<br>40 A 40 °C - 10 min for power circuit<br>84 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit   |
|---|--|
| Associated Fuse Rating                      | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>50 A gG at <= 690 V coordination type 1 for power circuit<br>35 A gG at <= 690 V coordination type 2 for power circuit   |
| Average Impedance                           | 2.5 mOhm - Ith 25 A 50 Hz for power circuit  |
| Power Dissipation Per Pole                  | 2.5 W AC-1<br>0.8 W AC-3   |
| [Ui] Rated Insulation Voltage               | Power circuit: 690 V conforming to IEC 60947-4-1<br>Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified  |
| Overvoltage Category                        | III  |
| Pollution Degree                            | 3  |
| [Uimp] Rated Impulse Withstand<br>Voltage   | 6 kV conforming to IEC 60947   |
| Safety Reliability Level                    | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO<br>13849-1  |
| Mechanical Durability                       | 30 Mcycles   |
| Electrical Durability                       | 1.65 Mcycles 18 A AC-3 at Ue <= 440 V<br>1 Mcycles 32 A AC-1 at Ue <= 440 V  |
| Control Circuit Type                        | DC standard  |
| Coil Technology                             | With integral suppression device   |
| Control Circuit Voltage Limits              | 0.10.25 Uc (-4070 °C):drop-out DC<br>0.71.25 Uc (-4060 °C):operational DC<br>11.25 Uc (6070 °C):operational DC   |
| Inrush Power In W                           | 5.4 W (at 20 °C)   |
| Hold-In Power Consumption In W              | 5.4 W at 20 °C   |
| Operating Time                              | 63 ±15 % ms closing<br>20 ±20 % ms opening   |
| Time Constant                               | 28 ms  |
| Maximum Operating Rate                      | 3600 cyc/h 60 °C   |
| Connections - Terminals                     | Control circuit: spring terminals 1 2.5 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: spring terminals 2 2.5 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: spring terminals 1 4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: spring terminals 2 4 mm <sup>2</sup> - cable stiffness: flexible without cable end |
| Auxiliary Contact Composition               | 1 NO + 1 NC  |
| Auxiliary Contacts Type                     | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1   |
| Signalling Circuit Frequency                | 25400 Hz   |
| Minimum Switching Voltage                   | 17 V for signalling circuit  |
| Minimum Switching Current                   | 5 mA for signalling circuit  |
| Insulation Resistance                       | > 10 MOhm for signalling circuit   |
| Non-Overlap Time                            | <ul><li>1.5 ms on de-energisation between NC and NO contact</li><li>1.5 ms on energisation between NC and NO contact</li></ul>   |
|   |  |

| Mounting Support | Plate<br>Rail   |  |
|------------------|-----------------|--|
| Environment      |                 |  |
| Standards        | CSA C22.2 No 14 |  |
|                  | EN 60947-4-1    |  |
|                  | EN 60947-5-1    |  |
|                  | IEC 60947-4-1   |  |
|                  | IEC 60947-5-1   |  |
|                  | UL 508          |  |

|  | UL 508   |
|--|--|
| Product Certifications                                   | CCC<br>DNV<br>GOST<br>UL<br>LROS (Lloyds register of shipping)<br>BV<br>GL<br>CSA<br>RINA  |
| Ip Degree Of Protection                                  | IP20 front face conforming to IEC 60529  |
| Protective Treatment                                     | TH conforming to IEC 60068-2-30  |
| Climatic Withstand                                       | conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat   |
| Permissible Ambient Air<br>Temperature Around The Device | -4060 °C<br>6070 °C with derating  |
| Operating Altitude                                       | 03000 m  |
| Fire Resistance  | 850 °C conforming to IEC 60695-2-1   |
| Flame Retardance   | V1 conforming to UL 94   |
| Mechanical Robustness                                    | Vibrations contactor open (2 Gn, 5300 Hz)<br>Vibrations contactor closed (4 Gn, 5300 Hz)<br>Shocks contactor open (10 Gn for 11 ms)<br>Shocks contactor closed (15 Gn for 11 ms) |
| Height   | 99 mm  |
| Width  | 45 mm  |
| Depth  | 101 mm   |
| Net Weight   | 0.49 kg  |

### **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 11.4 cm |
| Package 1 Width              | 10.5 cm |
| Package 1 Length             | 5.4 cm  |
| Package 1 Weight             | 510 g   |

## **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |