# **Product datasheet**

Specification





# Circuit breaker, EasyPact MVS, 3 Poles, 1250A, 50kA, AC, MDO, ET6, drawout, manual

MVS12N3MW6L

### Main

Range	EasyPact	
Product Name	MVS12N	
Device Short Name	MVS12N	
Product Or Component Type	Circuit breaker	
Device Application	Distribution	
Poles Description	escription 3P	
Protected Poles Description	3P 3d	
[In] Rated Current	1250 A at 40 °C	
Network Type	AC	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz conforming to IEC 60947-2	
Breaking Capacity Code	N	
Suitability For Isolation	Yes conforming to IEC 60947-2	
Utilisation Category	Category B	
Trip Unit Name	ET6G	
Trip Unit Technology	Technology Electronic	
Trip Unit Rating 1250 A		

## Complementary

•		
Network Frequency	50/60 Hz	
Control Type	Manually operated	
Mounting Mode	Drawout	
Mounting Support	Base plate Rail	
Connection Position	Horizontal Vertical	
Location Of Connection	Rear	
[Ui] Rated Insulation Voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2	
[Uimp] Rated Impulse Withstand Voltage	12 kV conforming to IEC 60947-2	
Circuit Breaker Ct Rating	1250 A	
Breaking Capacity	50 kA Icu at 220440 V AC 50/60 Hz conforming to IEC 60947-2	
[Ics] Rated Service Breaking Capacity	50 kA (Ics) at 220440 V AC 50/60 Hz conforming to IEC 60947-2	

Mechanical Durability	20000 cycles (with maintenance) conforming to IEC 60947-2 10000 cycles (without maintenance) conforming to IEC 60947-2
Electrical Durability	Category B: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC
	60947-2 Category B: 4000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2
Connection Pitch	115 mm without spreader
Contact Position Indicator	Yes
[Icm] Rated Short-Circuit Making Capacity	105 kA (Icm) at 220440 V AC 50/60 Hz conforming to IEC 60947-2
[Icw] Rated Short-Time Withstand Current	50 kA (1 s) at 220440 V AC 50/60 Hz conforming to IEC 60947-2 42 kA (1 s) at 690 V AC 50/60 Hz conforming to IEC 60947-2
	25 kA (3 s) at 440/690 V AC 50/60 Hz conforming to IEC 60947-2
Trip Unit Protection Functions	LSIG
Protection Type	Short time short-circuit protection Earth fault
	Instantaneous short-circuit protection
	Overload protection (long time)
Fault Indication	Short-circuit Earth fault
	Overload
	Internal fault
Long Time Pick-Up Adjustment Type Ir	Adjustable 9 settings
Long Time Pick-Up Adjustment Range	0.41 x ln
Long Time Delay Adjustment Type	Adjustable 9 settings
[Tr] Long-Time Delay Adjustment Range	0.524 s at 6 x lr
Short-Time Pick-Up Adjustment Type Isd	Adjustable 9 settings
[Isd] Short-Time Pick-Up Adjustment Range	1.510 x lr
Short-Time Delay Adjustment Type	Adjustable 5 settings
[Tsd] Short-Time Delay Adjustment Range	100400 ms
Instantaneous Pick-Up Adjustment Type Ii	Adjustable 9 settings
Instantaneous Pick-Up Adjustment Range	Off 215 x ln
Ground-Fault Pick-Up Adjustment	
Туре	Adjustable 9 settings
Ground-Fault Time Delay Adjustment Type -Tg	Adjustable 5 settings
[Tg] Ground-Fault Time Delay Adjustment Range	100400 ms
[Ig] Ground-Fault Pick-Up Adjustment Range	5001200 A
Zone Selective Interlocking Zsi	With
Current Sensor Rating Range	400/2000 A
Maximum Breaking Time	25 ms
Maximum Closing Response Time	70 ms
Height	439 mm
Width	441 mm
Depth	395 mm
Net Weight	70 kg

### **Environment**

Standards	IEC 60947-2	
Product Certifications	GOST CCC CCS EC	
Pollution Degree	4 conforming to IEC 60664-1	
Ip Degree Of Protection	IP40	
Ambient Air Temperature For Operation	-570 °C	
Ambient Air Temperature For Storage	-4085 °C without control unit -2585 °C with control unit	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	42.0 cm
Package 1 Width	35.0 cm
Package 1 Length	50.0 cm
Package 1 Weight	38.0 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes
	Pvc Free	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information