


Product datasheet

Specifications



M.PL.3-4V.WITHD.NS250 DEVICES

03421

⚠ Discontinued on: 9 Aug 2023

EAN Code: 3303430034216

⚠ Discontinued

Main

Range	Prisma
Range Of Product	Prisma P
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma P cubicle
Installation Description	Cubicle - width 650 mm depth 400 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Installed Device	ComPact: plug-in NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX250 with earth leakage protection - control: motor mechanism - vertical installation
Poles Description	4 x 3P: plug-in NSX100...160 vertical installation 3 x 4P: plug-in NSX100...160 vertical installation 2 x 3P: drawout NSX100...160 vertical installation 2 x 4P: drawout NSX100...160 vertical installation 4 x 3P: plug-in NSX250 vertical installation 3 x 4P: plug-in NSX250 vertical installation 2 x 3P: drawout NSX250 vertical installation 2 x 4P: drawout NSX250 vertical installation

Number Of Vertical Modules [50 Mm]	8 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle
	9 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle
	10 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle
	11 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle
	7 module(s): NSX100...160 without earth leakage protection , Linergy FC in 650 mm Widecubicle
	9 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle
	8 module(s): NSX250 without earth leakage protection , Linergy FC in 650 mm Widecubicle
	10 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle
	9 module(s): NSX100...160 with earth leakage protection , Linergy FC in 650 mm Widecubicle
	11 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle
	9 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle
	10 module(s): NSX250 with earth leakage protection , Linergy FC in 650 mm Widecubicle
	12 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle
	10 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle
Standards	IEC 61439-2
Product Certifications	ASEFA

Complementary

Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Smooth Matt
Colour	White
Width	603 mm
Height	202 mm
Depth	372 mm
Net Weight	3.2 kg

Functional Unit

[illegible]

650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in motor mechanism
vertical 4P 3 Linergy FC 10 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in toggle vertical 3P 4
direct 12 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in toggle vertical 4P 3
direct 12 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in direct front rotary
handle vertical 3P 4 direct 10 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in direct front rotary
handle vertical 4P 3 direct 10 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in motor mechanism
vertical 3P 4 direct 10 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in motor mechanism
vertical 4P 3 direct 10 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout toggle vertical 3P
2 direct 11 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout toggle vertical 4P
2 direct 11 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout direct front rotary
handle vertical 3P 2 direct 11 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout direct front rotary
handle vertical 4P 2 direct 11 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout motor mechanism
vertical 3P 2 direct 11 187.5 mm
650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout motor mechanism
vertical 4P 2 direct 11 187.5 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	21.000 cm
Package 1 Length	58.500 cm
Package 1 Weight	3.250 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	6
Package 2 Height	20.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	20.500 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	72
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	239.040 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free	
✓ Rohs Exemption Information	Yes
✓ Halogen Free Plastic Parts Product	

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information