Product datasheet

Specifications





(!) Discontinued

switch-disconnector NG125NA - 3 poles - 80 A

Local distributor code: 382140976

18890

() Discontinued on: 9 Feb 2023

EAN Code: 3303430188902

Main

Range	Acti9
Product Name	Acti9 NG125NA
Product Or Component Type	Switch disconnector
NG125NA	
Device Application	Distribution Making and breaking under load
Poles Description	3P
Number Of Protected Poles	3
Utilisation Category	AC-22A conforming to IEC 60947-3 AC-22B conforming to IEC 60947-3 AC-23B conforming to IEC 60947-3
Suitability For Isolation	Yes conforming to IEC 60947-3

Complementary

[le] Rated Operational Current	80 A at 500 V AC 50/60 Hz	
[Ue] Rated Operational Voltage	500 V AC 50/60 Hz	
[Icm] Rated Short-Circuit Making Capacity	2 kA switch-disconnector alone	
[Icw] Rated Short-Time Withstand Current	1.5 kA during 50 ms conforming to IEC 60947-3	
[Ui] Rated Insulation Voltage	age 690 V AC 50/60 Hz conforming to IEC 60947-3	
[Uimp] Rated Impulse Withstand Voltage		
Contact Position Indicator	Yes	
Control Type	Manual tripping test Toggle	
Local Signalling	ON/OFF indication Trip indicator	
Mounting Mode	Fixed	
Mounting Support	35 mm symmetrical DIN rail	
9 Mm Pitches	9	
Height	103 mm	
Width	81 mm	
Depth	81 mm	
Net Weight	0.72 kg	

Colour	Black	
Mechanical Durability	20000 cycles	
Electrical Durability	Category A (except AC20, DC20): 1500 cycles AC 50/60 Hz conforming to IEC 60947-3 Category B (except AC20, DC20): 300 cycles AC 50/60 Hz conforming to IEC 60947-3	
Provision For Padlocking	Padlockable	
Locking Options Description	Integrated padlocking	
Connections - Terminals	Tunnel type terminals (top or bottom) 1670 mm² rigid Tunnel type terminals (top or bottom) 1050 mm² flexible	
Wire Stripping Length	Power circuit: 20 mm for top or bottom connection	
Tightening Torque	Power circuit: 6 N.m top or bottom	

Environment

Standards	EN 60947-3 IEC 60947-3	
Product Certifications	VDE	
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 conforming to IEC 60529	
Ik Degree Of Protection	IK05	
Pollution Degree	3 conforming to IEC 60947-3	
Tropicalisation	2 conforming to IEC 60068-1	
Ambient Air Temperature For Operation	-1060 °C	
Ambient Air Temperature For Storage	-4070 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	12.0 cm
Package 1 Length	12.5 cm
Package 1 Weight	781.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	18
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	14.514 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information