

Product datasheet

Specifications



Acti9 control by illuminated push-buttons iATLz

A9C15413

Discontinued on: 4 Aug 2021

EAN Code: 3606480374869

Discontinued

Main

Range Of Product	Acti9
Device Short Name	iATLz
Product Or Component Type	Impedance adaptation auxiliary
[Uc] Control Circuit Voltage	130...240 V AC 50/60 Hz

Complementary

[Ui] Rated Insulation Voltage	440 V
[Uimp] Rated Impulse Withstand Voltage	4 kV
Remote Control Type	Illuminated push-button 3 mA
Mounting Mode	Fixed, on left side of TL
Mounting Support	DIN rail
9 Mm Pitches	2
Height	86 mm
Width	18 mm
Depth	71 mm
Colour	White
Connections - Terminals	Tunnel type terminals0.5...4 mm ² - rigid Tunnel type terminals0.5...4 mm ² - rigid - with cable end Tunnel type terminals1...4 mm ² - flexible Tunnel type terminals1...4 mm ² - flexible - with cable end
Wire Stripping Length	11 mm
Tightening Torque	1 N.m
Range Compatibility	Acti 9 Acti9 iTL iTL Acti 9 Acti9 iTL iTLi Acti 9 Acti9 iTL iTLs Acti 9 Acti9 iTL iTLc
Product Compatibility	ITL (32 A) ITL (16 A)

Environment

Overvoltage Category	III
Ip Degree Of Protection	IP20 conforming to IEC 60529
Tropicalisation	2
Relative Humidity	95 % at 55 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature For Operation	-20...50 °C
Ambient Air Temperature For Storage	-40...70 °C
Standards	EN/IEC 60669-2-2

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	1.800 cm
Package 1 Length	9.000 cm
Package 1 Weight	93.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	12
Package 2 Height	8.500 cm
Package 2 Width	9.200 cm
Package 2 Length	23.000 cm
Package 2 Weight	1.169 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	72
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	7.483 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations