Product datasheet





impulse relay iTLs - 1P - 1NO -16A - coil 12 VDC - 24 VAC 50/60Hz

Local distributor code: 396736127

A9C32111

EAN Code: 3606480092060

Main

Range Of Product	Acti9	
Product Name	Acti9 iTL	
Product Or Component Type	Impulse relay	
Device Short Name	iTLs	
Device Application	Remote indication	
Poles	1P	
Pole Contact Composition	1 NO	
Auxiliary Contact Composition	1 C/O	
[In] Rated Current	16 A	
Network Type	AC AC	
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz 12 V DC	

Complementary

Network Frequency	50/60 Hz	
[Ue] Rated Operational Voltage	250 V AC 50/60 Hz	
Control Type	Remote and manual control Coil deconnection	
Control Signal Type	Impulse	
Switching Frequency	100 switching operations/day 5 switching operations/minute	
Impulse Duration	50 ms1 s	
Remote Control Type	Illuminated push-button 3 mA	
Local Signalling	ON/OFF indication	
Signalling Circuit Voltage	AC: 24240 V DC: 24240 V	
Signalling Output Current	0.016 A	
Mounting Mode	Fixed	
Mounting Support	DIN rail	
9 Mm Pitches	2	
Height	84 mm	
Width	18 mm	

Life Is On Schneider 19 Apr 2024

Depth	60 mm AC-21: 200000 cycles AC-22: 100000 cycles	
Electrical Durability		
Connections - Terminals	Control circuit: tunnel type terminals 1 cable(s) 0.54 mm² rigid Control circuit: tunnel type terminals 1 cable(s) 0.54 mm² rigid with cable end Control circuit: tunnel type terminals 1 cable(s) 14 mm² flexible Control circuit: tunnel type terminals 1 cable(s) 14 mm² flexible with ferrule Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² rigid Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² rigid with cable end Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible with ferrule	
Wire Stripping Length	11 mm	
Tightening Torque	1 N.m	
Range Compatibility	Acti 9 iATEt Acti 9 iATLc Acti 9 iATLc+s Acti 9 iATLm Acti 9 iATLs Acti 9 iATLs Acti 9 iATLs Acti 9 iETL iTL 16 Acti 9 iATLc+c	

Environment

Standards	EN 669-2-2 EN 669-1
Product Certifications	CCC GOST
Quality Labels	CEBEC IMQ NF KEMA VDE
Noise Level	60 dB
Ip Degree Of Protection	IP20 conforming to IEC 60529 (on opening) IP40 conforming to IEC 60529 (in enclosure)
Pollution Degree	3
Tropicalisation	2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-2050 °C
Ambient Air Temperature For Storage	-4070 °C

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	1.800 cm
Package 1 Length	9.500 cm
Package 1 Weight	114.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	12
Package 2 Height	8.000 cm
Package 2 Width	9.500 cm

Package 2 Length	23.000 cm
Package 2 Weight	1.423 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	144
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	17.671 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations