Specifications





# variable speed drive - 1.5kW-400V - 3 phases - ATV340

Ethernet

Local distributor code: 408900540

ATV340U15N4E

EAN Code: 3606480966996

### Main

Range Of ProductAltivar Machine ATV3Product Or Component TypeVariable speed driveProduct Specific ApplicationMachineVariantStandard versionMounting ModeCabinet mountCommunication Port ProtocolModbus serial EtherNet/IP Modbus TCPNetwork Number Of Phases3 phasesSupply Frequency5060 Hz +/- 5 %[Us] Rated Supply Voltage380480 V - 1510 SNominal Output Current4.0 AMotor Power Kw2.2 kW for normal dut 1.5 kW for heavy dutyMotor Power Hp3 hp for normal duty 2 hp for heavy duty	40
Product Specific Application       Machine         Variant       Standard version         Mounting Mode       Cabinet mount         Communication Port Protocol       Modbus serial EtherNet/IP Modbus TCP         Network Number Of Phases       3 phases         Supply Frequency       5060 Hz +/- 5 %         [Us] Rated Supply Voltage       380480 V - 1510 S         Nominal Output Current       4.0 A         Motor Power Kw       2.2 kW for normal dut 1.5 kW for heavy duty         Motor Power Hp       3 hp for normal duty	
Variant       Standard version         Mounting Mode       Cabinet mount         Communication Port Protocol       Modbus serial EtherNet/IP Modbus TCP         Network Number Of Phases       3 phases         Supply Frequency       5060 Hz +/- 5 %         [Us] Rated Supply Voltage       380480 V - 1510 G         Nominal Output Current       4.0 A         Motor Power Kw       2.2 kW for normal duty         1.5 kW for heavy duty       Motor Power Hp	
Mounting Mode       Cabinet mount         Communication Port Protocol       Modbus serial EtherNet/IP Modbus TCP         Network Number Of Phases       3 phases         Supply Frequency       5060 Hz +/- 5 %         [Us] Rated Supply Voltage       380480 V - 1510 9         Nominal Output Current       4.0 A         Motor Power Kw       2.2 kW for normal duty         1.5 kW for heavy duty         Motor Power Hp       3 hp for normal duty	
Communication Port Protocol       Modbus serial EtherNet/IP Modbus TCP         Network Number Of Phases       3 phases         Supply Frequency       5060 Hz +/- 5 %         [Us] Rated Supply Voltage       380480 V - 1510 S         Nominal Output Current       4.0 A         Motor Power Kw       2.2 kW for normal duty         1.5 kW for heavy duty         Motor Power Hp       3 hp for normal duty	
EtherNet/IP         Modbus TCP         Network Number Of Phases       3 phases         Supply Frequency       5060 Hz +/- 5 %         [Us] Rated Supply Voltage       380480 V - 1510 S         Nominal Output Current       4.0 A         Motor Power Kw       2.2 kW for normal dut 1.5 kW for heavy duty         Motor Power Hp       3 hp for normal duty	
Supply Frequency       5060 Hz +/- 5 %         [Us] Rated Supply Voltage       380480 V - 1510 %         Nominal Output Current       4.0 A         Motor Power Kw       2.2 kW for normal duty         1.5 kW for heavy duty         Motor Power Hp       3 hp for normal duty	
[Us] Rated Supply Voltage     380480 V - 1510 S       Nominal Output Current     4.0 A       Motor Power Kw     2.2 kW for normal dut 1.5 kW for heavy duty       Motor Power Hp     3 hp for normal duty	
Nominal Output Current     4.0 A       Motor Power Kw     2.2 kW for normal dut 1.5 kW for heavy duty       Motor Power Hp     3 hp for normal duty	
Motor Power Kw       2.2 kW for normal dut         1.5 kW for heavy duty         Motor Power Hp       3 hp for normal duty	6
1.5 kW for heavy duty           Motor Power Hp         3 hp for normal duty	
	/
Emc Filter Class C3 EMC filter in	
Ip Degree Of Protection IP20	tegrated

# Complementary

Discrete Input Number	5 PTI programmable as pulse input: 030 kHz, 24 V DC (30 V) DI1DI5 safe torque off, 24 V DC (30 V), impedance: 3.5 kOhm programmable	
Discrete Input Type		
Number Of Preset Speeds	16 preset speeds	
Discrete Output Number	2.0	
Discrete Output Type	Programmable output DQ1, DQ2 30 V DC 100 mA	
Analogue Input Number	2	
Analogue Input Type	<ul> <li>Al1 software-configurable current: 020 mA, impedance: 250 Ohm, resolution 12 bits</li> <li>Al1 software-configurable temperature probe or water level sensor</li> <li>Al1 software-configurable voltage: 010 V DC, impedance: 31.5 kOhm, resolution 12 bits</li> <li>Al2 software-configurable voltage: - 1010 V DC, impedance: 31.5 kOhm, resolution 12 bits</li> </ul>	
Analogue Output Number	2	

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Analogue Output Type	Software-configurable voltage AQ1: 010 V DC impedance 470 Ohm, resolution 10 bits Software-configurable current AQ1: 020 mA impedance 500 Ohm, resolution 10 bits	
Relay Output Number	2	
Output Voltage	<= power supply voltage	
Relay Output Type	Relay outputs R1A Relay outputs R1C electrical durability 100000 cycles Relay outputs R2A Relay outputs R2C electrical durability 100000 cycles	
Maximum Switching Current	Relay output R1C on resistive load, cos phi = 1: 3 A at 250 V AC Relay output R1C on resistive load, cos phi = 1: 3 A at 30 V DC Relay output R1C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R1C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V DC Relay output R2C on resistive load, cos phi = 1: 5 A at 250 V AC Relay output R2C on resistive load, cos phi = 1: 5 A at 30 V DC Relay output R2C on resistive load, cos phi = 1: 5 A at 30 V DC Relay output R2C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R2C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC	
Minimum Switching Current	Relay output R1B: 5 mA at 24 V DC Relay output R2C: 5 mA at 24 V DC	
Physical Interface	2-wire RS 485	
Connector Type	3 RJ45	
Method Of Access	Slave Modbus RTU Slave Modbus TCP	
Transmission Rate	4.8 kbit/s 9.6 kbit/s 19.2 kbit/s 38.4 kbit/s	
Transmission Frame	RTU	
Number Of Addresses	1247	
Data Format	8 bits, configurable odd, even or no parity	
Type Of Polarization	No impedance	
4 Quadrant Operation Possible	True	
Asynchronous Motor Control Profile	Constant torque standard Optimized torque mode Variable torque standard	
Synchronous Motor Control Profile	Permanent magnet motor Reluctance motor	
Pollution Degree	2 conforming to IEC 61800-5-1	
Maximum Output Frequency	0.599 kHz	
Acceleration And Deceleration Ramps	Linear adjustable separately from 0.019999 s S, U or customized	
Motor Slip Compensation	Adjustable Not available in permanent magnet motor law Can be suppressed Automatic whatever the load	
Switching Frequency	216 kHz adjustable 816 kHz with derating factor	
Nominal Switching Frequency	4 kHz	
Braking To Standstill	By DC injection	
Brake Chopper Integrated	True	
Line Current	5.1 A at 380 V (normal duty) 4.1 A at 480 V (normal duty) 6.0 A at 380 V (heavy duty) 4.9 A at 480 V (heavy duty)	

Line Current	6 A at 380 V without line choke (heavy duty)	
	4.9 A at 480 V without line choke (heavy duty)	
	5.1 A at 380 V with external line choke (normal duty)	
	4.1 A at 480 V with external line choke (normal duty)	
	3.5 A at 380 V with external line choke (heavy duty)	
	2.8 A at 480 V with external line choke (heavy duty)	
Maximum Input Current	6.0 A	
Maximum Output Voltage	480 V	
Apparent Power	3.8 kVA at 480 V (normal duty)	
	4.1 kVA at 480 V (heavy duty)	
Maximum Transient Current	6.2 A during 60 s (normal duty)	
	6 A during 60 s (heavy duty)	
	7.6 A during 2 s (normal duty)	
	7.2 A during 2 s (heavy duty)	
Electrical Connection	Comming along an arts of a second starting and	
	Screw terminal, clamping capacity: 1.54 mm <sup>2</sup> for line side	
	Screw terminal, clamping capacity: 46 mm <sup>2</sup> for DC bus	
	Screw terminal, clamping capacity: 1.54 mm <sup>2</sup> for motor	
	Screw terminal, clamping capacity: 0.22.5 mm <sup>2</sup> for control	
Prospective Line Isc	5 kA	
Base Load Current At High Overload	4.0 A	
Base Load Current At Low Overload	5.6 A	
Power Dissipation In W	Natural convection: 46 W at 380 V, switching frequency 4 kHz (heavy duty)	
	Forced convection: 46 W at 380 V, switching frequency 4 kHz (heavy duty)	
	Natural convection: 59 W at 380 V, switching frequency 4 kHz (normal duty)	
	Forced convection: 59 W at 380 V, switching frequency 4 kHz (normal duty)	
Electrical Connection	Line side: screw terminal 1.54 mm²/AWG 14AWG 12	
	DC bus: screw terminal 46 mm²/AWG 12AWG 10	
	Motor: screw terminal 1.54 mm²/AWG 14AWG 12	
	Control: screw terminal 0.22.5 mm²/AWG 24AWG 12	
With Safety Function Safely Limited Speed (SIs)	True	
With Safety Function Safe Brake Management (Sbc/Sbt)	True	
With Safety Function Safe Operating Stop (Sos)	False	
With Safety Function Safe Position (Sp)	False	
With Safety Function Safe Programmable Logic	False	
With Safety Function Safe Speed Monitor (Ssm)	False	
With Safety Function Safe Stop 1 (Ss1)	True	
With Sft Fct Safe Stop 2 (Ss2)	False	
With Safety Function Safe Torque Off (Sto)	7 True	
With Safety Function Safely Limited Position (Slp)	False	
With Safety Function Safe Direction (Sdi)	False	

Protection Type	Thermal protection: motor		
	Safe torque off: motor		
	Motor phase loss: motor		
	Thermal protection: drive		
	Safe torgue off: drive		
	Overheating: drive		
	Overcurrent: drive		
	Output overcurrent between motor phase and earth: drive		
	Output overcurrent between motor phases: drive Short-circuit between motor phase and earth: drive Short-circuit between motor phases: drive Motor phase loss: drive		
	Line supply overvoltage: drive		
	Line supply undervoltage: drive		
	Input supply loss: drive		
	Exceeding limit speed: drive		
	Break on the control circuit: drive		
Width	05.0		

Width	85.0 mm
Height	270.0 mm
Depth	232.5 mm
Net Weight	1.7 kg
Continuous Output Current	5.6 A at 4 kHz for normal duty 4 A at 4 kHz for heavy duty

# Environment

Operating Altitude	<= 3000 m with current derating above 1000m	
Operating Position	Vertical +/- 10 degree	
Product Certifications	UL CSA TÜV EAC CTick	
Marking	CE	
Standards	IEC 61800-3 IEC 61800-5-1 IEC 60721-3 IEC 61508 IEC 13849-1 UL 618000-5-1 UL 508C	
Assembly Style	With heat sink	
Electromagnetic Compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6	
Environmental Class (During Operation)	Class 3C3 according to IEC 60721-3-3 Class 3S3 according to IEC 60721-3-3	
Maximum Acceleration Under Shock Impact (During Operation)	70 m/s² at 22 ms	
Maximum Acceleration Under Vibrational Stress (During Operation)	5 m/s² at 9200 Hz	
Maximum Deflection Under Vibratory Load (During Operation)	1.5 mm at 29 Hz	
Permitted Relative Humidity (During Operation)	Class 3K5 according to EN 60721-3	
Volume Of Cooling Air	18.0 m3/h	
Type Of Cooling	Forced convection	
Overvoltage Category	Class III	

Regulation Loop	Adjustable PID regulator
Noise Level	55.4 dB
Pollution Degree	2
Ambient Air Transport Temperature	-4070 °C
Ambient Air Temperature For Operation	-1550 °C without derating (vertical position) 5060 °C with derating factor (vertical position)
Ambient Air Temperature For Storage	-4070 °C
Isolation	Between power and control terminals

# **Packing Units**

0	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	37.000 cm
Package 1 Length	32.000 cm
Package 1 Weight	2.480 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	14
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	47.720 kg

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### **Resource performance**

Upgraded Components Available

### Well-being performance

Mercury Free

Rohs Exemption Information Yes

## **Certifications & Standards**


Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Circularity Profile	End of Life Information	

# ATV340U15N4E

### **Dimensions Drawings**


#### Dimensions

### Views: Front - Left - Rear



Mounting and Clearance

### Clearance



#### Dimensions in mm


X1	X2	X3
≥ <sub>100</sub>	≥ <sub>100</sub>	≥ <sub>60</sub>

#### Dimensions in in.

X1	X2	Х3
≥ <sub>3.94</sub>	≥ <sub>3.94</sub>	≥ <sub>2.36</sub>


#### Mounting Types

#### Mounting Type A: Side by Side IP20



Possible, at ambient temperature ≤ 50 °C (122 °F)

#### Mounting Type B: Individual IP20



a <sup>≥</sup> 50 mm (1.97 in.) from 50...60°C, no restriction below 50°C


## ATV340U15N4E

### Connections and Schema

#### **Connections and Schema**


# Three-phase Power Supply with Upstream Breaking via Line Contactor Without Safety Function STO

Connection diagrams conforming to standards ISO13849 category 1 and IEC/EN 61508 capacity SIL1, stopping category 0 in accordance with standard IEC/EN 60204-1.




- (1) Use relay output R1 set to operating state Fault to switch Off the product once an error is detected.
- A1: Drive
- KM1 : Line Contactor
- Q2, Q3 : Circuit breakers
- S1: Pushbutton
- S2 : Emergency stop
- T1: Transformer for control part

Three-phase Power Supply With Downstream Breaking via Switch Disconnector




- (1) Use relay output R1 set to operating state Fault to switch Off the product once an error is detected.
- A1: Drive
- Q1 : Switch disconnector

### **Sensor Connection**



It is possible to connect either 1 or 3 sensors on terminals Al1.


#### **Control Block Wiring Diagram**




- (1) 24V supply (STO)
- (2) STO Safe Torque Off
- (3) PTI Pulse Train In
- (4) PTO Pulse Train Out
- (5) Motor Encoder connection
- (6) Digital outputs
- (7) Digital inputs
- (8) Analog output
- (9) Analog input
- (10) Differential Analog Input
- (11) Ethernet port (only on Ethernet drive version)
- SW1 : Sink/Source switch
- R1A, R1B, R1C : Fault relay
- R2A, R2C : Sequence relay

#### **Digital Inputs Wiring**


Digital Inputs: Internal Supply Using DISUP Signal




In SRC position DISUP outputs 24 V. In SK position DISUP is connected to 0 V.



### **Digital Inputs: External Supply**




Digital Inputs: Internal supply Negative Logic, Sink, Asian Style



#### **Digital Outputs Wiring**


### Digital Outputs: Internal Supply

Positive Logic, Source, European Style, DQCOM to +24V



(1) Relay or valve


Negative Logic, Sink, Asian Style, DQCOM to 0V



(1) Relay or valve

#### Digital Outputs: External Supply


Positive Logic, Source, European Style, DQCOM to +24V



(1) Relay or valve

Negative Logic, Sink, Asian Style, DQCOM to 0V


ATV340U15N4E



(1) Relay or valve


### Performance Curves

### **Open Loop Applications**



- 1: Self-cooled motor: continuous useful torque
- 2: Force-cooled motor: continuous useful torque
- 3: Overtorque for 60 s maximum
- 4: Transient overtorque for 2 s maximum
- 5: Torque in overspeed at constant power

#### **Closed Loop Applications**



- 1: Self-cooled motor: continuous useful torque
- 2: Force-cooled motor: continuous useful torque
- 3: Overtorque for 60 s maximum
- 4: Transient overtorque for 2 s maximum
- 5: Torque in overspeed at constant power