

Product datasheet

Specifications



enclosed variable speed drive ATV61Plus - 250 kW-400V - IP54- simplified version

ATV61ES5C25N4

⚠ Discontinued on: 30 Jul 2021

⚠ To be end-of-service on: 31 Dec 2024

⚠ Discontinued

EAN Code: 3606485215174

Main

Range Of Product	Altivar 61 Plus
Product Or Component Type	Variable speed drive
Device Short Name	ATV61
Product Destination	Synchronous motors Asynchronous motors
Product Specific Application	Pumping and ventilation machine
Assembly Style	Ready to use In floor-standing enclosure with separate air flows
Product Composition	ATV61HC25N4 drive on heatsink An IP65 remote mounting kit for graphic display terminal A DC choke Circuit breaker Motor terminals A wired ready-assembled Sarel Spacial 6000 enclosure A plinth
Emc Filter	Integrated
Network Number Of Phases	3 phases
Rated Supply Voltage	380...415 V +/- 10 %
Supply Frequency	50...60 Hz
Motor Power Kw	250 kW, 3 phases at 380...415 V
Line Current	418 A at 400 V3 phases / 250 kW
Ip Degree Of Protection	IP54

Complementary

Apparent Power	292 kVA for 400 V3 phases / 250 kW
Prospective Line Isc	50 kA with external fuses
Continuous Output Current	481 A at 2.5 kHz, 400 V3 phases
Maximum Transient Current	577 A for 60 s 3 phases
Speed Drive Output Frequency	0.1...500 Hz
Nominal Switching Frequency	2.5 kHz
Switching Frequency	2...8 kHz adjustable 2.5...8 kHz with derating factor
Speed Range	1...100 in open-loop mode, without speed feedback

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Speed Accuracy	+/- 10 % of nominal slip 0.2 Tn to Tn without speed feedback
Torque Accuracy	+/- 15 % in open-loop mode, without speed feedback
Transient Overtorque	120 % of nominal motor torque for 60 s 135 % of nominal motor torque for 2 s
Braking Torque	30 % without braking resistor ≤ 125 % with braking resistor
Asynchronous Motor Control Profile	Voltage/frequency ratio, 2 points Voltage/frequency ratio, 5 points Voltage/frequency ratio - Energy Saving, quadratic U/f Flux vector control without sensor, standard
Synchronous Motor Control Profile	Vector control without sensor, standard
Regulation Loop	Adjustable PI regulator
Motor Slip Compensation	Automatic whatever the load Adjustable Not available in voltage/frequency ratio (2 or 5 points) Suppressable
Supply Voltage Limits	342...457 V
Network Frequency Limits	47.5...63 Hz
Overvoltage Category	Class 3 conforming to EN 50178
Local Signalling	LCD display unit for operation function, status and configuration
Output Voltage	≤ supply voltage
Isolation	Electrical between power and control
Type Of Cable For External Connection	IEC cable at 40 °C, copper 70 °C / PVC
Electrical Connection	Terminal - 2.5 mm² / AWG 14 (AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR) Terminal M10 - 2 x 300 mm² (L1/R, L2/S, L3/T) Terminal M12 - 4 x 240 mm² (U/T1, V/T2, W/T3)
Motor Recommended Cable Cross Section	2 (3 x 150) mm²
Short-Circuit Protection	630 A fuse protection type gI - power supply upstream
Supply	External supply: 24 V (19...30 V)DC, <1 A Internal supply for reference potentiometer: 10 V (10...11 V)DC, <10 A Internal supply: 24 V (21...27 V)DC, <100 A
Analogue Input Number	2
Analogue Input Type	AI2 software-configurable voltage: 0...10 V DC, 24 V max, impedance: 30 kOhm, sampling time: 1.5...2.5 ms, resolution: 11 bits AI1-/AI1+ bipolar differential voltage: +/- 10 V DC, 24 V max, sampling time: 1.5...2.5 ms, resolution: 11 bits + sign AI2 software-configurable current: 0...20 mA/4...20 mA, impedance: 250 Ohm, sampling time: 1.5...2.5 ms, resolution: 11 bits
Analogue Output Number	1
Analogue Output Type	Software-configurable voltage: (AO1) 0...10 V DC - 470 Ohm - sampling time: 1.5...2.5 ms - resolution: 10 bits Software-configurable current: (AO1) 0...20 mA/4...20 mA - 500 Ohm - sampling time: 1.5...2.5 ms - resolution: 10 bits
Discrete Output Number	2
Discrete Output Type	Configurable relay logic: (R1A, R1B, R1C)NO/NC - 6.5...7.5 ms - 100000 cycles Configurable relay logic: (R2A, R2B)NO - 6.5...7.5 ms - 100000 cycles
Minimum Switching Current	3 mA at 24 V DC (configurable relay logic)
Maximum Switching Current	5 A at 250 V AC on resistive load - cos phi = 1 for configurable relay logic 2 A at 30 V DC on inductive load - L/R = 7 ms for configurable relay logic 5 A at 30 V DC on resistive load - L/R = 0 ms for configurable relay logic 2 A at 250 V AC on inductive load - cos phi = 0.4 for configurable relay logic

Discrete Input Number	7
Discrete Input Type	Programmable (LI1...LI5) at 24 V DC <= 30 V level 1 PLC 3.5 kOhm (duration=1.5... 2.5 ms) Switch-configurable (LI6) at 24 V DC <= 30 V level 1 PLC 1.5 kOhm (duration=1.5... 2.5 ms) Safety input (PWR) at 24 V DC <= 30 V 1.5 kOhm
Discrete Input Logic	Positive (PWR), 0...2 V (state 0), 17...30 V (state 1) Positive (LI1...LI6), 0...5 V (state 0), 11...30 V (state 1) Negative (LI1...LI6), 16...30 V (state 0), 0...10 V (state 1)
Acceleration And Deceleration Ramps	S, U or customized Linear adjustable separately from 0.01 to 9000 s
Braking To Standstill	By DC injection, <60 s
Protection Type	Overheating protection: drive Thermal protection: drive Short-circuit between motor phases: drive Input phase breaks: drive Overcurrent between output phases and earth: drive Overvoltages on the DC bus: drive Break on the control circuit: drive Against exceeding limit speed: drive Line supply undervoltage: drive Line supply overvoltage: drive Against input phase loss: drive Thermal protection: motor Motor phase break: motor Power removal: drive Power removal: motor
Dielectric Strength	3535 V DC between earth and power terminals 5092 V DC between control and power terminals
Insulation Resistance	> 1 mOhm 500 V DC for 1 minute
Frequency Resolution	Display unit: 0.1 Hz Analog input: 0.024/50 Hz
Communication Port Protocol	CANopen Modbus
Connector Type	1 RJ45 (on front face) for Modbus 1 RJ45 (on terminal) for Modbus Male SUB-D 9 on RJ45 for CANopen
Physical Interface	2-wire RS 485 for Modbus
Transmission Frame	RTU for Modbus
Transmission Rate	9600 bps, 19200 bps for Modbus on front face 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps for Modbus on terminal 20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps for CANopen
Data Format	8 bits, 1 stop, even parity for Modbus on front face 8 bits, odd even or no configurable parity for Modbus on terminal
Type Of Polarization	No impedance for Modbus
Number Of Addresses	1...247 for Modbus 1...127 for CANopen
Method Of Access	Slave CANopen
Operating Position	Vertical +/- 10 degree
Colour Of Enclosure	Light grey (RAL 7035)
Colour Of Base Of Enclosure	Dark grey (RAL 7022)
Width	800 mm
Height	2362 mm
Depth	642 mm
Net Weight	440 kg

Environment

Electromagnetic Compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11
Standards	EN 61800-3 environments 1 category C3 EN 55011 class A group 2 EN/IEC 61800-5-1 EN 61800-3 environments 2 category C3 EN/IEC 61800-3
Product Certifications	ATEX GOST
Marking	CE
Noise Level	72 dB
Pollution Degree	3 conforming to EN/IEC 61800-5-1
Vibration Resistance	1.5 mm (f= 3...10 Hz) conforming to EN/IEC 60068-2-6 0.6 gn (f= 10...200 Hz) conforming to EN/IEC 60068-2-6 3M3 conforming to EN/IEC 60721-3-3
Shock Resistance	4 gn for 11 ms conforming to EN/IEC 60068-2-27 3M2 conforming to EN/IEC 60721-3-3
Environmental Characteristic	3C2 without condensation conforming to IEC 60721-3-3 3S2 without condensation conforming to IEC 60721-3-3 3K3 without condensation conforming to IEC 60721-3-3
Relative Humidity	0...95 %
Ambient Air Temperature For Operation	0...40 °C (without derating) 40...50 °C (with current derating of 2 % per °C)
Ambient Air Temperature For Storage	-25...70 °C
Volume Of Cooling Air	1400 m3/h
Operating Altitude	<= 1000 m without derating 1000...3000 m with current derating 1 % per 100 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	240.0 cm
Package 1 Width	62.0 cm
Package 1 Length	82.0 cm
Package 1 Weight	440.0 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	1
Package 2 Height	260.0 cm
Package 2 Width	90.0 cm
Package 2 Length	100.0 cm
Package 2 Weight	480.0 kg


Contractual warranty

Warranty	18 months
----------	-----------

Dimensions Drawings

Ready to Use IP 54 Enclosure

Dimensions




NOTE: For each floor-standing enclosure added, allow a 4 mm/0.15 in. space for the seal.

Connections and Schema

Ready to Use IP 54 Enclosure

Wiring Diagram



- A1 Drive
- A2 Enclosure
- L1 DC choke
- M Motor
- Q1 Circuit breaker
- (1) Filter
- (2) Control
- (3) Relay control
- (4) Reference potentiometer
- (5) PLC


Performance Curves

Ready to Use IP 54 Enclosure

Derating Curves

The derating curves for the drive nominal current (In) are dependent on the temperature and switching frequency. For intermediate temperatures, interpolate between 2 curves.

NOTE: The drive will reduce the switching frequency automatically in the event of excessive temperature rise.



X Switching frequency (kHz)

NOTE: The temperatures shown correspond to the temperature of the air entering the enclosure.