# **Product datasheet**





## PowerPact-circuit breaker-25A 4P AC 65kA at 480/440V(UL/IEC)-TMD-compression lug

BJF46025

! End-of-service on: 12 May 2021

! Discontinued

EAN Code: 3606481150721

#### Main

Range	PowerPact
Product Name	PowerPact B
Device Short Name	BJ 025
Product Or Component Type	Circuit breaker
Device Application	Distribution

### Complementary

[In] Rated Current	25 A
Number Of Poles	4P
Protected Poles Description	4t
Control Type	Toggle
Breaking Capacity Code	J
Breaking Capacity	100 kA at 208Y/120 V AC 50/60 Hz conforming to UL 489 100 kA at 240 V AC 50/60 Hz conforming to UL 489 65 kA at 480/277 V AC 50/60 Hz conforming to UL 489 65 kA at 480 V AC 50/60 Hz conforming to UL 489 25 kA at 600Y/347 V AC 50/60 Hz conforming to UL 489 50 kA at 250 V DC conforming to UL 489
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz conforming to UL 489
Network Frequency	50/60 Hz
[Ics] Rated Service Breaking Capacity	100 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 500525 V AC 50/60 Hz conforming to IEC 60947-2 2.5 kA at 690 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947-2
Trip Unit Technology	Thermal-magneticTM-D,
Continuous Current Rating	80 %
[Ui] Rated Insulation Voltage	800 V conforming to IEC 60947-2
Trip Unit Name	TM-D
Suitability For Isolation	Yes conforming to IEC 60947-2
Utilisation Category	Category A
Mechanical Durability	15000 cycles conforming to IEC 947-1 Annex K ed 5.2
Electrical Durability	10000 cycles conforming to IEC 947-1 Annex K ed 5.2 at 440 V In

Life Is On Schneider 4 May 2024



Connection Pitch	27 mm	
Awg Gauge	AWG 14AWG 8 aluminium/copper AWG 6AWG 3/0 aluminium/copper	
Local Signalling	Presence of auxiliary contacts: flag (green)	
Mounting Mode	Clip-on (35 mm symmetrical DIN rail) By screws (plate)	
Electrical Connection	Terminal nut, ON and OFF end	
Tightening Torque	5 N.m for 2.516 mm² (AWG 14AWG 4) 9 N.m for 2595 mm² (AWG 3AWG 3/0)	
Number Of Slots	1 slot(s) for auxiliary switch OF (plug-in) 1 slot(s) for voltage release MN or MX (plug-in) 1 slot(s) for alarm switch SD (plug-in)	
Power Wire Stripping Length	20 mm	
Color	Grey (RAL 7016)	
9 Mm Pitches	12	
Height	137 mm	
Width	108 mm	
Depth	80 mm	
Net Weight	1.241 kg	
Quantity Per Set	Set of 1	
Circuit Breaker Application	HACR rated	

### **Environment**

Quality Labels	CE
Standards	UL 489 NEMA AB1 GB 14048.2 CSA C22.2 No 5 NMX J-266 EN/IEC 60947-2 EN/IEC 60947-5-1
Product Certifications	UL IEC CCC EAC CSA NOM
Ip Degree Of Protection	Front cover: IP40 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 62262
Pollution Degree	3 conforming to IEC 60947-1
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-5085 °C
Operating Altitude	2000 m without derating 5000 m with derating

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.43 cm

Package 1 Width	12.7 cm	
Package 1 Length	20.32 cm	
Package 1 Weight	1.814 kg	

## **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	
<b>⊘</b>	Halogen Free Product	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

4 May 2024