# **Product datasheet**





### Galaxy VS UPS 20kW 400V, 1 internal 9Ah smart modular battery string, expandable to 4, Start-up 5x8

GVSUPS20KB4HS

#### Overview

Presentation	Highly efficient, easy-to-deploy 20kW, 400V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 1 smart high-capacity modular battery string, expandable to 4 strings for extended runtime. Runtime charts available in the Documents tab.
Lead Time	Usually Ships within 2 Weeks
Main	
Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated Power In W	20 kW
Rated Power In Va	20 kVA
Output Connector Type	Hard wire 5-wire (3P + N + E) 1
Battery Type	Internal modular battery VRLA
Provided Equipment	Battery modules ship installed Dust filter EcoStruxure IT ready (UPS)

### **Batteries & Runtime**

Efficiency	View Efficiency Graph ☐
Battery Voltage	480 V
Discharge Battery Voltage	384 V DC
Max Current Discharge	54 A
Battery Power In Vah	0 VAh runtime
Extended Runtime	0

Installation guide

Start-up service

Integrated network management Power modules ship installed

### **General**

Bypass Voltage Tolerance	+/- 10 %
Redundant	No

# **Physical**

Colour	White
Height	148.5 cm
Width	52.1 cm
Depth	84.7 cm
Net Weight	320 kg
Usb Compatible	No

# Input

<u> </u>	
Network Frequency	4070 Hz
Number Of Input Connectors	1 hard wire 4-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	340460 V 400 V
Maximum Input Current	36 A
Max Short Time Withstand Current	65 kA
Input Harmonic Distortion	Less than 3 % for full load
Load Power Factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor At Full Load	0.99

# Output

•	
Maximum Configurable Power In W	20 kW
Harmonic Distortion	Less than 3 %
Output Frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest Factor	2.5
Wave Type	Sine wave
Output Voltage Tolerance	+/-1% after 50ms
Output Harmonic Distortion	< 1% linear load and < 3% non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Bypass Type	Built-in static bypass
Maximum Configurable Power In Va	20 kVA

### Conformance

Product Certifications	UL 1778 5th edition
Standards	CSA C22.2 No 107.3 EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 IEC 60721-4-2 level 2M2

### **Environmental**

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 % non-condensing

Operating Altitude	03281 ft
Ambient Air Temperature For Storage	-1540 °C
Storage Relative Humidity	095 % non-condensing
Storage Altitude	0.003048.00 m
Acoustic Level	55 dBA
Heat Dissipation	2431 Btu/h
Ip Degree Of Protection	IP20

### **Communications & Management**

Free Slots	1
Control Panel	Touch screen LCD user interface

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	168 cm
Package 1 Width	99 cm
Package 1 Length	64 cm
Package 1 Weight	360 kg

### **Contractual warranty**

Warranty 1 year repair or replace

# Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

#### Resource performance

Energy Efficient Product

✓ Take-Back Program Available

### Well-being performance

Mercury Free

Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

China Rohs Regulation

China RohS declaration

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information

25 Apr 2024