## **Product datasheet**

Specification





# integrated servo motor - 2.2 Nm - 6000 rpm - multiturn - without brake

ILM0703P02A0000

EAN Code: 3606485293936

#### Main

Range Of Product	PacDrive 3
Product Or Component Type	Servo motor integrated drive
Device Short Name	ILM

#### Complementary

Complementary		
[Us] Rated Supply Voltage	250700 V	
Continuous Stall Current	3 A	
Continuous Stall Torque	2.2 N.m	
Peak Stall Torque	8.7 N.m	
Nominal Output Power	720 W	
Nominal Torque	1.15 N.m	
Nominal Speed	6000 rpm	
Maximum Current Irms	12 A	
[In] Rated Current	1.5 A	
Shaft End	Untapped	
Second Shaft	Without second shaft end	
Shaft Diameter	aft Diameter 14 mm	
Shaft Length 30 mm		
Key Width	20 mm	
Feedback Type	Absolute multiturn SinCos Hiperface	
Speed Feedback Resolution	128 periods	
Holding Brake	Without	
Mounting Support	International standard flange	
Motor Flange Size	70 mm	
Torque Constant	0.76 N.m/A at 120 °C	
Back Emf Constant	49 V/krpm at 20 °C	
Number Of Motor Poles	6	
Rotor Inertia	0.58 kg.cm²	
Stator Resistance	2.7 Ohm at 20 °C for Ph/Ph 1.88 Ohm at 120 °C for Ph/N	
Stator Inductance	13 mH at 20 °C for Ph/Ph 6.5 mH at 120 °C for Ph/N	

Maximum Radial Force Fr	730 N at 1000 rpm
	580 N at 2000 rpm
	510 N at 3000 rpm
	460 N at 4000 rpm
	430 N at 5000 rpm
	400 N at 6000 rpm
Maximum Axial Force Fa	0.2 x Fr
Type Of Cooling	Natural convection
Length	259 mm
Number Of Motor Stacks	3
Centring Collar Diameter	60 mm
Centring Collar Depth	2.5 mm
Number Of Mounting Holes	4
Mounting Holes Diameter	5.5 mm
Circle Diameter Of The Mounting Holes	82 mm
Net Weight	4.2 kg

#### **Environment**

Ip Degree Of Protection IP54

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	20.0 cm
Package 1 Width	26.5 cm
Package 1 Length	59.0 cm
Package 1 Weight	5.645 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	8
Package 2 Height	77.0 cm
Package 2 Width	80.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	53.66 kg

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Mercury Free	
<b>Ø</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information