

Thorsman - TP 16 - plug - without screw - set of 10

IMT38064

! Discontinued on: 12 Jul 2023

EAN Code: 3606480335044

Main

Range Of Product	Thorsman	
Product Or Component Type	Wall plug	
Device Short Name	TP	
Device Application	Lightweight installation	
Drilling Diameter	16 mm concrete	
Minimum Drilling Depth	88 mm	
Screw Diameter	12 mm	
Material	PEHD (polyethylene high density)	

Complementary

Practical Load Capacity	Shear: 5 kN for concrete C25 4.5) Pull-out load: 3 kN for concrete C25 6)	
Practical Load Capacity	Shear: 500 kg for concrete C25 4.5) Pull-out load: 300 kg for concrete C25 6)	
Colour Tint	Orange	
Ambient Air Temperature For Operation	-5080 °C	
Diameter	16 mm	
Length	80 mm	

Environment

Quantity Per Set	Set of 10
Sale Per Indivisible Quantity	1
Net Weight	0.0107 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.600 cm
Package 1 Width	1.600 cm
Package 1 Length	8.000 cm
Package 1 Weight	1.000 g
Unit Type Of Package 2	P12

Number Of Units In Package 2	9600
Package 2 Height	80.000 cm
Package 2 Width	105.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	126.840 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations