
Product datasheet

Specification





KT 5X800AL FEED UNIT ER N3

KTA0800ER53

EAN Code: 3606485210261

Main

Range	Canalis	
Product Name	КТ	
Product Or Component Type	Flatwise elbow feeder trunking	
Device Short Name	KTA	
Device Application	Feeder length	
Supply	Oil-immersed transformer Switchboard	
Material	Aluminium	
[le] Rated Operational Current	800 A at 35 °C	
Neutral Position	Down	
Direction Change Type	direction 1: edgewise to left	
Earth Conductor	Reinforced	
Short-Circuit Level	Standard version	
Provided Equipment	Trunking unit	

Complementary

Housing Material	Polyester film	
Contacts Material	Copper	
[Ue] Rated Operational Voltage	1000 V	
Network Frequency	50/60 Hz	
[Ui] Rated Insulation Voltage	1000 V	
[Icw] Rated Short-Time Withstand Current	31 kA	
[lpk] Rated Peak Withstand Current	64 kA	
Radiated Magnetic Field	0.4 μΤ	
Thermal Stress Limit	961000 kA².s	
Thdi	015 % 800 A 1533 % 1000 A 33100 % 1250 A	
Maximum Voltage Drop	<0.0083 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0081 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0076 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0069 V with power factor = 0.7 at 50 Hz with 1A for 100 m long	
Mounting Mode	By screws	
Mounting Support	Plate	

Polarity	3L + N + PER	
Number Of Tap-Off Outlets	0	
Standards	IEC 61439-6 IEC 61439-1	
Dimension Type	Made to measure	
Connection Pitch	80250 mm	
Depth	230 mm	
Height	direction 1: 200534 mm	
Length	direction 2: 300 mm	
Colour	White (RAL 9001)	
Linear Load	13 kg/m	

Environment

Ip Degree Of Protection	IP55 conforming to IEC 60529	
Ik Degree Of Protection	Protection IK08 conforming to IEC 62262	
Derating Factor	035 °C (100 % of In) 3540 °C (97 % of In) 4045 °C (93 % of In) 4550 °C (90 % of In) 5055 °C (86 % of In)	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	80.0 cm
Package 1 Width	23.0 cm
Package 1 Length	95.0 cm
Package 1 Weight	30.0 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information