# **Product datasheet**

Specification





# TeSys D - time delay auxiliary contact block - 1 NO + 1 NC screw clamp terminals

Local distributor code: 381818490

LADT4

EAN Code: 3389110385977

#### Main

Main	
Range	TeSys TeSys Deca
Product Name	TeSys Deca
Product Or Component Type	Time delay auxiliary contact block
Range Compatibility	TeSys Deca CAD TeSys Deca LC1D TeSys F LC1F TeSys F CR1F
Mounting Location	Front
Pole Contact Composition	1 NO + 1 NC
Contacts Operation	Time delay
Timer Type	On delay
Time Delay Range	10180 s
[Ue] Rated Operational Voltage	690 V AC 25400 Hz
[le] Rated Operational Current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-5-1 600 V conforming to UL 60947-5-1 600 V conforming to CSA C22.2 No 60947-5-1
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C)
Standards	EN/IEC 60947-5-1 GB/T 14048.5
Product Certifications	IECEE CB Scheme UL CSA CCC EAC UKCA

## Complementary

•		
Irms Rated Making Capacity	140 A at <= 690 V AC conforming to IEC 60947-5-1	
	250 A at <= 690 V DC conforming to IEC 60947-5-1	
Permissible Short-Time Rating	100 A 60 °C 1 s	
	120 A 60 °C 500 ms	
	140 A 60 °C 100 ms	
Protection Type	GG fuse 10 A	
Mechanical Durability	5 Mcycles	
Minimum Switching Current	5 mA	

Minimum Switching Voltage	17 V
Non-Overlap Time	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact
	·
Insulation Resistance	> 10 MOhm
Connections - Terminals	Screw clamp terminals 1 cable(s) 12.5 mm²flexible with cable end
	Screw clamp terminals 1 cable(s) 12.5 mm²flexible without cable end
	Screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end
	Screw clamp terminals 2 cable(s) 12.5 mm²flexible without cable end
	Screw clamp terminals 1 cable(s) 12.5 mm²rigid
	Screw clamp terminals 2 cable(s) 12.5 mm²rigid
	Screw clamp terminals
Tightening Torque	1.7 N.m - with screwdriver flat Ø 6 mm
	1.7 N.m - with screwdriver Philips No 2
	1.7 N.m - with screwdriver pozidriv No 2
Height	48 mm
Width	44 mm
Depth	61 mm
olour Dark grey	

## **Environment**

Environmental Characteristic	Normal environment
Ip Degree Of Protection	IP20 conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Storage	-6080 °C
Ambient Air Temperature For Operation	-4070 °C
Operating Altitude	3000 m

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	6.5 cm
Package 1 Length	5.0 cm
Package 1 Weight	74.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	5.2 cm
Package 2 Width	14.0 cm
Package 2 Length	24.0 cm
Package 2 Weight	750.0 g
Unit Type Of Package 3	S03
Number Of Units In Package 3	140
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm

Package 3 Weight

10.988 kg

## **Contractual warranty**

Warranty

18 months

# Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations